WHOI-78-70

REMOTE ACOUSTIC MONITORING OF NATURAL SUSPENSATE DISTRIBUTIONS,
ACTIVE SUSPENSATE RESUSPENSION, AND SLOPE/SHELF WATER INTRUSIONS

by

Marshall H. Orr
and
Frederick R. Hess

WOODS HOLE OCEANOGRAPHIC INSTITUTION
Woods Hole, Massachusetts 02543

October 1978

TECHNICAL REPORT

*Prepared for the Naval Oceanic Research and
Development Activity under Contract N00014-77-C-0196.*

*Reproduction in whole or in part is permitted
for any purpose of the United States Government.
In citing this report in a bibliography, the
reference given should be to the "Journal of
Geophysical Research, Vol. 83, No. C8, August 20,
1978", pp. 4062-4068".*

*Approved for public release; distribution un-
limited.*

Approved for Distribution: Earl E. Hays, Chairman
Department of Ocean Engineering

Remote Acoustic Monitoring of Natural Suspensate Distributions, Active Suspensate Resuspension, and Slope/Shelf Water Intrusions

MARSHALL H. ORR AND FREDERICK R. HESS

Department of Ocean Engineering, Woods Hole Oceanographic Institution, Woods Hole, Massachusetts 02543

Acoustic data, transmissometer data, and calculations are presented which indicate that high-frequency acoustic backscattering systems can become a valuable tool in the remote monitoring of suspended particle distributions and active resuspension areas. Data are also presented which show that acoustic backscattering systems can be used to remotely detect slope/shelf water frontal zones. Towed acoustic systems should be able to map the extent of the frontal zone and add significantly to the understanding of frontal zone processes.

INTRODUCTION

Standard physical oceanographic instrumentation, i.e., CTD, XBT, and water bottle sampling, provides discrete measurements of water mass properties which can be difficult to interpret because of the lack of vertical and/or horizontal information between data points. Acoustic backscattering systems (ABSS) can monitor vertical and horizontal sections of the water column on a continuous basis. The acoustic data in conjunction with the discrete measurements can allow a more complete interpretation of the physics, i.e., internal wave interactions, mixing processes, water mass interleaving, and the horizontal extent of isothermal or isopycnal surfaces. This article presents acoustic backscattering data which demonstrate the capability of ABSS to provide continuous information about changing water mass properties.

Acoustic backscattering in the water column can be caused by the presence of particles (both animate and inanimate), thermal structure, and turbulence. In nearly isothermal water masses, such as those associated with some areas of the benthic boundary layer (BBL), particles should be the dominant scattering mechanism. In areas of slope/shelf water intrusions or frontal zones, thermal backscattering and backscattering from turbulence and particles can contribute to the reflected acoustic energy. Calculations of the scattering cross sections expected from isotropic and layered temperature fluctuations have been adapted to the ocean from models applied to atmospheric turbulent mixing processes [Munk and Garrett, 1973; Proni and Apel, 1975]. Simple calculations for the acoustic backscattering cross section expected from clayey silt distributions are presented here.

Recently, high-frequency (20–200 kHz) ABSS have been used to study the distributions of particles or suspensates introduced into the oceans as a result of man's activities, e.g., harbor dredging, sewage sludge disposal, and chemical waste disposal [Proni *et al.*, 1976a; Proni *et al.*, 1976b; Orr and Hess, 1978]. Although naturally occurring fluid mud layers ($>> 10$ mg/l) have been detected with multifrequency acoustic systems [Tsuchiya *et al.*, 1973; Gallene, 1973], very little work has been done using acoustic systems to monitor naturally occurring suspensates (≥ 5 μ g/l) and, in particular, those suspensates originating from or found in the vicinity of the BBL. It should be noted that acoustic systems have been used to detect layers of turbidity in freshwater lakes [Schroeder *et al.*, 1964]. This article presents data which indicate that acoustic systems can detect variations in naturally occurring suspended particle distributions.

The vertical and horizontal distribution of particles in the ocean, the response of the nepheloid layer associated with the BBL to perturbations, and the relationship of these responses to changes in bedform morphology are current research topics. The particles in the ocean are known to occur with a wide range of size, composition, density [McCave, 1975], and compressibility. Their concentration is from 5 μ g/l to greater than 10 mg/l. Their size can be from less than 1 μ m to greater than 120 μ m. Their composition may be either entirely inorganic or organic, or a combination of the two. The concentration and size distribution of oceanic particles are presently determined at discrete locations and depths by filtering water obtained with Niskin bottles and analyzing the filters. The particle distribution can be detected in situ at discrete locations and/or depths with nephelometers and transmissometers. With calibration, ABSS can be used to obtain continuous quantitative measurements of suspensate concentration and distribution for a vertical section of the water column either from a stationary or a moving vessel and/or a fixed platform. When the acoustic systems are used in such a manner, they can serve as a complementary tool to transmissometers and nephelometers.

Frontal zone processes are presently studied with CTD sensors and associated Niskin bottle samplers, XBT's, fine structure probes [Gregg, 1975], and neutrally buoyant floats [Voorhis *et al.*, 1976]. Each of the data sampling techniques provides information about the properties of the water column at a discrete location or depth. To understand properly the frontal zone processes, continuous time series of vertical sections of the water column are needed. This is particularly important when events of short duration and limited vertical scale occur at the frontal zone. Data are presented here which show that ABSS can continuously monitor slope/shelf water frontal zones.

In frontal zone areas the measured magnitude of the backscattered acoustic signals in conjunction with CTD measurements and water samples will provide an estimate of the magnitude of the backscattering caused by particles and the thermal properties of the water. If areas of turbulent mixing are observed, the magnitude of the backscattered acoustic signals may be compared to the magnitudes predicted by theory. An estimate of the temperature structure factor of the mixing event may be obtained.

CALCULATION OF ANTICIPATED SENSITIVITY OF AN ACOUSTIC SYSTEM FOR DETECTION OF CLAYEY SILT DISTRIBUTIONS

Acoustic backscattering from a particle is influenced by the size, geometric configuration, density, and compressibility of

the particle and the frequency of the acoustic signal. Very little information exists on the distribution of sizes of particles in the ocean and their density. Even less information on their compressibility is available. Indeed, active discussion is presently underway as to the importance of various sized particles to the mass flux to the ocean bottom [McCave, 1975]. To determine the magnitude of the backscattering levels which could be encountered in the ocean, calculations are presented for clayey silt particles of known radius and density. It is assumed that the particles are uniformly but individually distributed throughout a volume.

The ability to detect scattered acoustic energy is limited by the magnitude of the acoustic background noise. The background noise level of a 200-kHz transducer is determined in the ideal case by the thermal motion or Brownian motion of the molecules in seawater. Picking an attenuation constant (the constant is temperature dependent) for 200-kHz sound in seawater, the acoustic energy which is projected into the water column, the bandwidth of the acoustic signal, the transmit and receive beam patterns of the transducer being used, the pulse length, and the calculated thermal noise band level at the face of a transducer, one can estimate the magnitude of the smallest scattered acoustic signal which can be detected above thermal noise as a function of range from the transducer. Knowing the magnitude of the acoustic signal which can be detected, one can determine the smallest target or number of individual targets of known geometry and physical character which may be detected by an ideal acoustic system. The reader interested in performing these calculations should consult a standard acoustics text [Urlick, 1967].

Figure 1 indicates the smallest target strength which will produce an acoustic signal 3 dB above thermal noise at a stated range for a 200-kHz acoustic transducer with an ideal conical beam pattern of 2.5° and a source level of 233 dB re 1 μ Pa at 1 m (see the labeled horizontal lines). The curves have

Fig. 1. Calculated acoustic target strength versus particle concentration for clayey silt spheres of varying radius and known density and compressibility. The spheres were assumed to be uniformly distributed throughout a volume of 1 m³. The minimum target strength which can be detected by a 200-kHz ABSS as a function of range from the target is drawn on the figure (dashed horizontal line) for ranges of 10, 50, 100, and 200 m. A detection threshold of 3 dB was assumed. Corrections have been included for the beamwidth of the transducer (2.5°). A source level of 233 dB re 1 μ Pa at 1 m and a pulse width of 200 μ s have been assumed. The values of γ_k and γ_p used in the calculations were -0.56 and 0.77 , respectively.

been corrected for volume effects as a function of range assuming that the scatterers are uniformly distributed throughout the volume. The target strength (in decibels) per cubic meter versus concentration (in micrograms per liter) of a uniform distribution of individual spherical clayey silt scatterers of known radius has also been plotted in Figure 1. The sensitivity of the acoustic system to uniformly distributed clayey silt as a function of range and particle concentration can be read from the graph.

Target strength is defined as $TS = 10 \log I_s/I_i$, where I_s is the intensity of backscattered acoustic energy at 1 m from the target and I_i is the intensity of the acoustic energy incident on the target.

The ratio of the backscattered acoustic energy to the incident acoustic energy for a distribution of spherical scatterers is calculated from the following [Morse and Ingard, 1968] equation:

$$\frac{I_s}{I_i} \approx \frac{1}{9} \frac{NV}{r^2} a^6 k^4 (\gamma_k + \gamma_p \cos \theta)^2$$

where

$$\gamma_k = (\kappa_e - \kappa)/\kappa \quad \gamma_p = (3\rho_e - 3\rho)/z_p$$

and

- κ_e compressibility of the sphere;
- ρ_e density of the sphere;
- κ compressibility of the water;
- ρ density of the water;
- a radius of the sphere;
- k wave number of the acoustic signal;
- N total number of scatterers per unit volume;
- V volume of the insonified section of the water column;
- r distance of the scatterer or group of scatterers from the receiver;
- θ angle between the plane wave propagation vector of the incident energy and the direction of the scattered radiation.

The values of γ_k and γ_p used in the calculations are -0.56 and 0.77 , respectively. It is assumed that the individual scatterers are uniformly distributed throughout the volume and are not clustered together as aggregates. The scattered acoustic intensities from each individual scatterer are added together. To date, no experimental confirmation of the Rayleigh backscattering theory for large numbers of small particles ($\lambda \gg a$) per unit volume has been found in the literature for acoustic signals in the frequency range of 200–10,000 kHz.

As can be seen (Figure 1), an ideal 200-kHz ABSS may be able to detect the presence of tens of micrograms of clayey silt scatterers with diameters of $\approx 200 \mu$ m or greater at a range of 100 m. The acoustic systems presently in use at this laboratory are thought to be sensitive to target strengths of the order of -100 dB at 100 m. The exact sensitivity will be determined once the systems are fully calibrated.

RESULTS

Continental Shelf

Acoustic backscattering data were obtained (December 28–29, 1976) at three stations (stations 4, 5, and 6) (Figures 2a–2c), each separated by 21.8 km along a track (Figure 3) nearly due south from Nantucket Island and at a separate station (station 7) (Figure 2d) southeast of the island during the Woods Hole Oceanographic Institution (WHOI) R/V

Fig. 2. Two-hundred-kHz backscattering data, depth versus time, from four separate data stations taken over the continental shelf south of Nantucket Island. See Figure 3 for the geographic location of the stations. The acoustic fish was suspended from a boom on the port side of the *Oceanus* at a depth of 1 m. The ocean bottom reflection shows up at each station as a black band; e.g., station 4 bottom depth is at ≈ 45 m. The small variations (≈ 1 m) in the bottom depth are caused by ship roll. The gray scale or darkness recorded on the graphics paper between the surface (0 m) and the ocean bottom is caused by backscattering from particles in the water column. The variation in the darkness of the records is proportional to the magnitude of the acoustic signal which is reflected by the scatterers in the water column. The graphic paper had a 20-dB dynamic range; i.e., no signal (white paper) to the maximum recordable signal (black paper) represents a signal amplitude variation by a factor of 10. Since particle concentration is proportional to signal amplitude squared, the paper could show a factor of 100 variation in the total number of identical particles present per unit volume at a particular depth (assuming that Rayleigh backscattering theory is correct). The no-signal color level of the paper is pointed out below the bottom reflected signal of station 4, arrow 1. Variation in the gray scale level at a particular depth from station to station is caused by variation in the total number or variety of particles per unit volume at that depth; e.g., compare the station 4 gray scale level at a depth of ≈ 20 m (particle concentration 2.71 mg/l) to the station 7 gray scale level at a depth of ≈ 25 m (particle concentration 0.44 mg/l). Note the decreasing gray scale level from stations 4, 5, 6, and 7 at ≈ 20 -m depth, indicating a decreasing particle concentration level at each station. The decreasing gray scale of the acoustics record from station to station (i.e., decreasing particle concentration) corresponds to increasing optical transmission; see Figure 4. (a) Station 4. The highest suspended particle burdens were found at this station. Note the difference in gray scale levels at a fixed depth (e.g., 30 m) and the decreasing particle concentrations found at this depth from station to station. Also note the variability of scattering as a function of time at station 4 (arrows 2 and 3, depth of ≈ 37 –45 m), indicating a patchy structure to the particle distribution in the water column. (b) Station 5. A strong scattering layer (≈ 7 m thick) at a depth of 45–55 m was detected. The particle concentration, when the gray scale level of stations 4 and 5 are intercompared at the same depth, would be expected to be in excess of 2.9 mg/l. The feature was observed in the transmissometer records (Figure 4, station 5, arrow 1). (c) Station 6. A slope/shelf water intrusion zone (upper edge 58–70 m in depth) was detected at this station. The transmissometer data (Figure 4) and the temperature, salinity, and σ_T data (Figure 5) detected a slope water intrusion beneath the isothermal isohaline shelf water. The interface of the two water masses is clearly distinguished in the acoustic record (arrow 4). Note the vertical oscillation of the interface as a function of time. There is an enhanced acoustic scattering layer (≈ 7 m thick, arrow 5) extending below the interface. Below this layer the acoustic scattering remains relatively uniform in gray scale level (arrow 6). The difference in suspended particle concentration above and below the interface was about 1.2 mg/l. The suspended particle concentration at 60 m was determined from water taken above the slope/shelf water interface. (d) Station 7. The lowest suspended particle concentrations were observed at this station.

Oceanus cruise 20. Water samples were obtained with Niskin bottles attached to a CTD near the bottom, middepth, and surface to determine the total suspended solid burden by filtering through $0.45\text{-}\mu\text{m}$ Millipore filters (John Milliman, WHOI). The depths at which the water samples were taken are noted by the arrows in Figure 2. The particle concentrations (in milligrams per liter) found at those depths are also noted in Figure 2.

In addition, CTD and transmissometer (Figure 4) measurements were obtained at each station (Michael Bothner, U.S. Geological Survey, Woods Hole, Massachusetts). With the exception of station 6 (Figure 3) the water column was isothermal and isohaline. The temperature, computed salinity, and σ_T for station 6 are plotted in Figure 5.

The acoustics data were taken at each station with the same total system and time-varying gain (compensates for transmission loss). Any variation in gray scale between the individual stations or as a function of time at station is caused by a variation in the acoustic scattering. The maximum gain of the acoustic system was not used during these experiments because of the large particulate concentrations found at stations 4 and 5. The dynamic range of the time-varying gain was limited and did not compensate for attenuation loss, which was approximately 6×10^{-2} dB/m. Thus the gray scale or darkness of the recording on the graphics recorder paper will be lighter for the deeper of two identical scatterers. This point will be considered in the following discussions.

Each station was maintained for a 1- to 2-hour period. The

Fig. 3. Map indicating the geographic location of each of the data stations shown in Figure 2.

Oceanus drifted at a speed between 0.25 and 0.5 m/s. The acoustic fish was within 1 m of the surface. The water was acoustically sampled 480 times per minute.

Only a small fraction, ≈ 20 -min sections, of the continuous acoustic record obtained at each station is presented (Figure 2). Each of the acoustic records displayed was obtained within a few minutes of the CTD, transmissometer, and water sample measurements.

Station 4 (Figure 2a) had a total suspended load burden which increased with depth, i.e., $2.38 \rightarrow 2.95$ mg/l. The gray scale of the acoustics record is fairly uniform and has some lightening with depth, as is anticipated from the characteristics of the time-varying gain in the system. The alternating broad vertical dark and light bands are an artifact of the graphics recorder used. It was corrected before the remaining stations were occupied. The gray scale difference between station 4 (Figure 2a) and the other stations (Figures 2b–2d) is apparent. The difference in the total measured particle concentration at similar depths between the stations and the difference in acoustic record gray scale indicate a decreasing suspended particle concentration between stations 4, 5, 6, and 7. The transmissometer data obtained at station 4 indicate a decreasing transmission to a depth of 20 m with fairly uniform transmission below that depth (Figure 4). The transmission measured at station 4 was the lowest for each of the occupied stations. As was mentioned, the acoustic record presents 480 samples of the water column per minute. The transmissometer record is a single sample. The acoustic record does not show the presence of any continuous horizontal horizon, which indicates that the deviations from the trend in the transmissometer records are only local to that section of the water column sampled.

Station 5 (Figure 2b) with 65 m of water is interesting, as the concentrations of the suspended burden were lower than those of the previous station, and a dense scattering area which was oscillating vertically with respect to the ocean bottom was detected acoustically. The scattering layer was also detected by the transmissometer (Figure 6, arrow 1), indicating a correlation between the two particle detectors. The scattering area was found to nearly touch the bottom on occasion and to reach the displacement indicated in the figure on other occasions. The transmissometer data indicate that the layer was separated from the bottom, as the relative transmission at the bottom was higher than that within the layer. Intercomparison of graphic recorder gray scales obtained at similar depths (≈ 45 m) at stations 4 and 5 indicates that the acoustic scattering layer detected at station 5 should have a suspended solid burden in excess of 2.9 mg/l. Unfortunately, the acoustic system was not accompanied during this cruise with an analog

magnetic tape recorder such that acoustic intensities may be intercompared between stations. The data do indicate that without the acoustic system the presence of this scattering area or nepheloid layer which has been detached from the bottom would be missed with discrete water sampling systems unless close attention was given to the transmissometer measurements. The acoustics complements the transmissometer, as it provides both continuous horizontal and vertical coverage of the water column. The change of the relative transmission measured by the transmissometer in the area of large acoustic scattering was of the same magnitude as some deviations noted in station 4. Only repeated lowerings of the transmissometer would have confirmed the presence of the enhanced particle concentration. The acoustic system easily indicated the presence of the layers. It is not known if the scattering area was of animate or inanimate nature. Water samples and biological samples were not taken from the scattering area. The station was occupied from 1935 to 2050 LT, or more than 2 hours following sunset on an overcast day. If the layer had been animate, one would not have expected it to be present. It has been our experience that most deeper animate scattering layers break up and move to the surface during the evening hours. The 200-kHz acoustic frequency used during this experiment has been used [McNaught, 1969] to measure zooplankton biomass in the Great Lakes. McNaught does not mention being able to detect inanimate objects in his article. Schroeder, however, does claim to be able to differentiate between zooplankton, phytoplankton, and very fine grain detritus introduced into lakes by rivers. It is our contention that this can also be done in the ocean. The transmissometer also cannot discern between animate and inanimate objects. An oscilloscope display of the acoustic signal from the scattering layer may allow a differentiation to be made between discrete biological scatterers and a diffuse suspended layer of detritus.

At station 6 (Figure 2c) a nepheloid layer (2 mg/l within 1 m of the bottom) was found to be associated with a lens of slope water which had intruded beneath the shelf water. The ABSS continuously monitored the presence of the nepheloid layer and the interface (arrow 4) between the shelf and slope water. Unlike the transmissometer system, which would have had to be continuously raised and lowered through the interface to observe changes in the interface displacement with respect to the bottom, the acoustics data remotely detected vertical displacements as large as 15 m. The interpretation of the acoustics data is strengthened following intercomparison with the transmissometer profile taken at station 6 (Figure 4). A sharp breakaway from the isothermal structure at about 70 m coincided with a decrease in transmission as measured by the

Fig. 4. Relative transmission as a function of depth for each of the stations displayed in Figure 2.

Fig. 5. The temperature, salinity, and σ_T for station 6. The σ_T for stations 4 and 5 is also included. The water at station 4 had a temperature of 5.85°C and a salinity of 32.8‰. The water at station 5 had a temperature of 4.15°C and a salinity of 32.4‰. Both stations were isothermal and isohaline.

transmissometer. A strongly enhanced area of acoustic backscattering is associated with the upper edge of the interface ≈ 7 m thick (arrow 5). A weaker scattering is noted below this interface zone (arrow 6). The temperature, salinity, and σ_T profiles for this station are displayed (Figure 5). Note the warmer, more saline wedge of slope water under the colder isothermal and isohaline shelf water. The increase in density at the boundary could cause particles to be trapped at the interface and could cause an increase in the level of the backscattered acoustic signal. Backscattering from the thermal gradient could also contribute to the detected acoustic signal. The gradient of the temperature is 0.44°C/m. For the concentration of particulates measured (2 mg/l) the acoustic target strength is extrapolated (Figure 1) to be -87 dB and -107 dB for particles of 100- μ m and 20- μ m diameter, respectively. Depending upon the backscattering model which is used, the calculated acoustic target strength for backscattering from the thermal gradient is also of the same magnitude. Thus the acoustic scattering cross section associated with the slope/shelf water interface could be contributed to by both the suspended solid burden and the thermal gradient. The shelf

break would appear a likely area to test the hypothesis [Munk and Garrett, 1973; Proni and Apel, 1975] concerning the possibility of using acoustic backscattering as a remote sensor of thermal gradients, their associated microstructure and turbulent mixing events, and the internal wave field interactions with the thermal gradient. This would be particularly true if areas of low suspended solids could be found and contrasted with areas of high suspended solids and similar thermal structure. It is important to note that even with the precise knowledge of the acoustic scattering mechanism, the acoustic system can be used to monitor continuously and map the fluid interactions at the shelf and slope water boundaries.

Station 7 (Figure 2d) is included to indicate that the acoustic system used during the *Oceanus* cruise was sensitive to 440 μ g/l (the lowest particle concentration encountered on the cruise) of suspended solids at ranges of at least 20 m. The relative optical transmission is also included for station 7 (Figure 4). The ultimate resolution of suspended particle concentration by the acoustic system will have to be determined in cleaner water during future cruises.

Estuary Environment

Figures 6 and 7 are representative of areas of active particulate resuspension and particulate distributions which have been detected with a 200-kHz ABSS in the estuary environment. The data were obtained in Buzzards Bay, Massachusetts, on March 21, 1977, approximately 3 hours after ebb tide. The average current in the locality of the data acquisition was about 0.2 m/s [Eldridge Tide and Pilot Book, 1977] to the south. The survey vessel was moving north at 1.5 m/s. An area of active resuspension of material from the bottom of the bay was detected (Figure 6, arrow 1). The vessel was turned to port to a southerly heading, and the area of active resuspension was again encountered (Figure 7, arrow 1). The resuspended material acts as a tag in the water column in a manner similar to that of dye in a laboratory flume experiment. The effects of topographic structures on the flow are evident (Figure 7, arrow 2). The resuspended material does not remain as a nepheloid layer near the bottom of the bay but is moved quite effectively into the near-surface waters. Apparently, a pathway exists for the transport of nutrients from the bay bottom to the surface. Past studies in the bay have not detected nutrient distributions which peaked near the surface [Rhoads and Young, 1970]. The acoustics data would indicate that further nutrient experiments downstream from the areas of active resuspension and over a complete tidal cycle during the various seasons should be performed to determine if the acoustically detected resuspended material provides a significant input of nutrients into

Fig. 6. Particle resuspension area detected in Buzzards Bay, Massachusetts, with the 200-kHz ABSS. Tidal flow was to the south. The boat was traveling to the north. The resuspension point is marked (arrow 1). Note that the particles were being transported to the surface of the bay (arrow 2).

Fig. 7. Particle resuspension area detected in Buzzards Bay, Massachusetts, with the 200-kHz ABSS. Tidal flow was to the south. The boat was traveling to the south. The resuspension point is marked (arrow 1). Note the influence of the topographic feature on the motion of the resuspended particles (arrow 2).

the bay surface waters. During the experiment period the bay waters are known to be mixed; there was a 5- to 10-m/s NW wind, and the surface waves were from 0.1 to 0.5 m in amplitude. If a seasonal thermocline existed in Buzzards Bay during the experiment, it should have acted as a barrier to the transport of the particulates to the surface waters. Divers have noted an increase in turbidity below the seasonal thermocline when it exists in Buzzards Bay.

CONCLUSION

Data and calculations have been presented which show that sensitive high-frequency ABSS can be used to remotely monitor frontal zones and suspended particle distributions in estuary and shelf water environments. The detection of active resuspension areas and nepheloid areas exhibiting vertical displacement and horizontal variability as a function of time indicates the usefulness of the acoustic systems in the continuous remote detection of the fluid bottom interaction processes associated with the estuary and continental shelf regimes. The acoustic systems need to be further refined in terms of the quantification of the backscattered intensity versus the total suspended solid burden. In addition, the reliability of the Rayleigh backscattering theory used in the target strength calculations must be determined through laboratory experimentation.

If the Rayleigh backscattering calculations are shown to be reliable in laboratory experiments, the remote ABSS could be incorporated into bottom-mounted stations to monitor, for extended periods, the variability of the nepheloid layer. When the acoustics data are correlated with Reynolds stress measurements, changes in bedform morphology and transmissometer data, an increased understanding of the interrelationships between fluid flow, bedform changes, and the nepheloid layer variability should be obtained.

The slope/shelf water intrusion data (Figure 2c) indicate that both an acoustic system moored to the ocean bottom and towed acoustic systems used near the shelf break should provide a wealth of information concerning the interaction of the slope/shelf water frontal zone and the associated nepheloid layer.

Acknowledgments. The authors wish to thank John D. Milliman (WHOI), who supplied the total particulate burden measurements which were included in Figure 2. We also express appreciation to Michael H. Bothner (Branch of Atlantic-Gulf of Mexico Geology, U.S. Geological Survey, Woods Hole, Massachusetts), who allowed us to use the transmissometer and CTD data displayed in Figures 4

and 5. The critical review and helpful suggestions of Earl E. Hays of WHOI are gratefully acknowledged. This article is WHOI contribution 3987. This work was supported by Naval Oceanic Research and Development Activity contract N00014-77-c-0196.

REFERENCES

- Eldridge Tide and Pilot Book, Robert Eldridge White, Boston, Mass., 1977.
- Gallenne, B., Study of fine material in suspension in the estuary of Loire and its dynamic grading, estuarine and coastal, *Mar. Sci.*, 2, 261-272, 1973.
- Gregg, M., Microstructure and intrusions in the California Current, *J. Phys. Oceanogr.*, 5, 253-278, 1975.
- McCave, I. N., Vertical flux of particles in the ocean, *Deep Sea Res.*, 22, 491-502, 1975.
- McNaught, D. C., Developments in acoustic plankton sampling, in *Proceedings of the Twelfth Conference on Great Lakes Research*, pp. 61-68, International Association of Great Lakes Research, 1969.
- Morse, P. M., and K. U. Ingard, *Theoretical Acoustics*, chap. 8, McGraw-Hill, New York, 1968.
- Munk, W. H., and C. J. R. Garrett, Internal wave breaking and microstructure, *Boundary Layer Meteorol.*, 4, 37-45, 1973.
- Orr, M. H., and F. R. Hess, Acoustic monitoring of industrial chemical waste released at deep water dump site 106, submitted to *J. Geophys. Res.*, 1978.
- Proni, J. R., and J. R. Apel, On the use of high-frequency acoustics for the study of internal waves and microstructure, *J. Geophys. Res.*, 80, 1147-1151, 1975.
- Proni, J. R., F. C. Newman, R. L. Sellers, and C. Parker, Acoustic tracking of ocean-dumped sewage sludge, *Science*, 193, 1005-1007, 1976a.
- Proni, J. R., F. C. Newman, D. C. Rona, D. E. Drake, G. A. Berberian, C. A. Lauter, Jr., and R. L. Sellers, On the use of acoustics for studying suspended oceanic sediment and for determining the onset of the shallow thermocline, *Deep Sea Res.*, 23, 831-836, 1976b.
- Rhoads, D. C., and D. K. Young, The influence of deposit-feeding organisms on sediment stability and community trophic structure, *J. Mar. Res.*, 28, 150-178, 1970.
- Schroeder, R., and H. Schroeder, On the use of the echo sounder in lake investigations, *Mem. Ist. Ital. Idrobiol.*, 17, 167-188, 1964.
- Tsuchiya, A., K. Ogawa, and M. Nishimura, Acoustical characteristics of underwater floating mud layer, *J. Fac. Mar. Sci. Tech. Toaki Univ.*, 7, 179-192, 1973.
- Urick, R. J., *Principles of Underwater Sound for Engineers*, McGraw-Hill, New York, 1967.
- Voorhis, A. D., D. C. Webb, and R. C. Millard, Current structure and mixing in the shelf/slope water front south of New England, *J. Geophys. Res.*, 81, 3695-3708, 1976.

(Received June 29, 1977;
revised February 21, 1978;
accepted February 22, 1978.)

MANDATORY DISTRIBUTION LIST

FOR UNCLASSIFIED TECHNICAL REPORTS, REPRINTS, & FINAL REPORTS
PUBLISHED BY OCEANOGRAPHIC CONTRACTORS
OF THE OCEAN SCIENCE AND TECHNOLOGY DIVISION
OF THE OFFICE OF NAVAL RESEARCH

(REVISED FEBRUARY 1978)

1	Director of Defense Research
and Engineering
Office of the Secretary of Defense
Washington, D.C. 20301
ATTN: Office Assistant Director
(Research)	1	National Oceanographic Data
Center
National Oceanic & Atmospheric
Administration
330C Whitehaven St., N.W.
Washington, D.C. 20235
	Office of Naval Research
Arlington, VA 22217	12	Defense Documentation
Center
Cameron Station
Alexandria, VA 22314
1	ATTN: (Code 460)		Commander
Naval Oceanographic
Office
Washington, D.C. 20373
1	ATTN: (Code 102-OS)	1	ATTN: Code 1640
1	ATTN: (Code 200)	1	ATTN: Code 70
1	CDR J. C. Harlett, (USN)
ONR Representative
Woods Hole Oceanographic Inst.
Woods Hole, MA 02543	3	NORDA 430
NSTL Station, MS 39529
1	Office of Naval Research
Branch Office
495 Summer Street
Boston, MA 02210	2	CO NORDA
NSTL Station, MS 39529
	Director
Naval Research Laboratory
Washington, D.C. 20375		
6	ATTN: Library, Code 2620		

UNCLASSIFIED 10/78

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER WHOI-78-70	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) REMOTE ACOUSTIC MONITORING OF NATURAL SUSPENSATE DISTRIBUTIONS, ACTIVE SUSPENSATE RESUSPENSION, AND SLOPE/SHELF WATER INTRUSIONS		5. TYPE OF REPORT & PERIOD COVERED Technical
		6. PERFORMING ORG. REPORT NUMBER WHOI CON. NO. 3987
7. AUTHOR(s) Marshall H. Orr and Frederick R. Hess		8. CONTRACT OR GRANT NUMBER(s) N00014-77-C-0196;
9. PERFORMING ORGANIZATION NAME AND ADDRESS Woods Hole Oceanographic Institution Woods Hole, MA 02543		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS NORDA National Space Technology Laboratory Bay St. Louis, MS 39529		12. REPORT DATE October 1978
		13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Reprinted from "Journal of Geophysical Research, Vol. 83, No. C8, August 20, 1978, pp. 4062-4068".		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) 1. Acoustics 2. Physical oceanography 3. Particulate distributions		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Acoustic data, transmissometer data, and calculations are presented which indicate that high-frequency acoustic backscattering systems can become a valuable tool in the remote monitoring of suspended particle distributions and active resuspension areas. Data are also presented which show that acoustic backscattering systems can be used to remotely detect slope/shelf water frontal zones. Towed acoustic systems should be able to map the extent of the frontal zone and add significantly to the understanding of frontal zone processes.		

<p>Woods Hole Oceanographic Institution WHOI-78-70</p> <p>REMOTE ACOUSTIC MONITORING OF NATURAL SUSPENSATE DISTRIBUTIONS, ACTIVE SUSPENSATE RESUSPENSION, AND SLOPE/SHELF WATER INTRUSIONS by Marshall H. Orr and Frederick R. Hess. Reprinted from "Journal of Geophysical Research, Vol. 83, No. C8, August 20, 1978, pp. 4062-4068". October 1978. Prepared for the Naval Oceanic Research and Development Activity under Contract N00014-77-C-0196.</p> <p>Acoustic data, transmissometer data, and calculations are presented which indicate that high-frequency acoustic backscattering systems can become a valuable tool in the remote monitoring of suspended particle distributions and active resuspension areas. Data are also presented which show that acoustic backscattering systems can be used to remotely detect slope/shelf water frontal zones. Towed acoustic systems should be able to map the extent of the frontal zone and add significantly to the understanding of frontal zone processes.</p>	<p>1. Acoustics</p> <p>2. Physical oceanography</p> <p>3. Particulate distributions</p> <p>I. Orr, Marshall H.</p> <p>II. Hess, Frederick R.</p> <p>III. N00014-77-C-0196</p> <p>This card is UNCLASSIFIED</p>	<p>Woods Hole Oceanographic Institution WHOI-78-70</p> <p>REMOTE ACOUSTIC MONITORING OF NATURAL SUSPENSATE DISTRIBUTIONS, ACTIVE SUSPENSATE RESUSPENSION, AND SLOPE/SHELF WATER INTRUSIONS by Marshall H. Orr and Frederick R. Hess. Reprinted from "Journal of Geophysical Research, Vol. 83, No. C8, August 20, 1978, pp. 4062-4068". October 1978. Prepared for the Naval Oceanic Research and Development Activity under Contract N00014-77-C-0196.</p> <p>Acoustic data, transmissometer data, and calculations are presented which indicate that high-frequency acoustic backscattering systems can become a valuable tool in the remote monitoring of suspended particle distributions and active resuspension areas. Data are also presented which show that acoustic backscattering systems can be used to remotely detect slope/shelf water frontal zones. Towed acoustic systems should be able to map the extent of the frontal zone and add significantly to the understanding of frontal zone processes.</p>	<p>1. Acoustics</p> <p>2. Physical oceanography</p> <p>3. Particulate distributions</p> <p>I. Orr, Marshall H.</p> <p>II. Hess, Frederick R.</p> <p>III. N00014-77-C-0196</p> <p>This card is UNCLASSIFIED</p>	<p>Woods Hole Oceanographic Institution WHOI-78-70</p> <p>REMOTE ACOUSTIC MONITORING OF NATURAL SUSPENSATE DISTRIBUTIONS, ACTIVE SUSPENSATE RESUSPENSION, AND SLOPE/SHELF WATER INTRUSIONS by Marshall H. Orr and Frederick R. Hess. Reprinted from "Journal of Geophysical Research, Vol. 83, No. C8, August 20, 1978, pp. 4062-4068". October 1978. Prepared for the Naval Oceanic Research and Development Activity under Contract N00014-77-C-0196.</p> <p>Acoustic data, transmissometer data, and calculations are presented which indicate that high-frequency acoustic backscattering systems can become a valuable tool in the remote monitoring of suspended particle distributions and active resuspension areas. Data are also presented which show that acoustic backscattering systems can be used to remotely detect slope/shelf water frontal zones. Towed acoustic systems should be able to map the extent of the frontal zone and add significantly to the understanding of frontal zone processes.</p>	<p>1. Acoustics</p> <p>2. Physical oceanography</p> <p>3. Particulate distributions</p> <p>I. Orr, Marshall H.</p> <p>II. Hess, Frederick R.</p> <p>III. N00014-77-C-0196</p> <p>This card is UNCLASSIFIED</p>
<p>Woods Hole Oceanographic Institution WHOI-78-70</p> <p>REMOTE ACOUSTIC MONITORING OF NATURAL SUSPENSATE DISTRIBUTIONS, ACTIVE SUSPENSATE RESUSPENSION, AND SLOPE/SHELF WATER INTRUSIONS by Marshall H. Orr and Frederick R. Hess. Reprinted from "Journal of Geophysical Research, Vol. 83, No. C8, August 20, 1978, pp. 4062-4068". October 1978. Prepared for the Naval Oceanic Research and Development Activity under Contract N00014-77-C-0196.</p> <p>Acoustic data, transmissometer data, and calculations are presented which indicate that high-frequency acoustic backscattering systems can become a valuable tool in the remote monitoring of suspended particle distributions and active resuspension areas. Data are also presented which show that acoustic backscattering systems can be used to remotely detect slope/shelf water frontal zones. Towed acoustic systems should be able to map the extent of the frontal zone and add significantly to the understanding of frontal zone processes.</p>	<p>1. Acoustics</p> <p>2. Physical oceanography</p> <p>3. Particulate distributions</p> <p>I. Orr, Marshall H.</p> <p>II. Hess, Frederick R.</p> <p>III. N00014-77-C-0196</p> <p>This card is UNCLASSIFIED</p>	<p>Woods Hole Oceanographic Institution WHOI-78-70</p> <p>REMOTE ACOUSTIC MONITORING OF NATURAL SUSPENSATE DISTRIBUTIONS, ACTIVE SUSPENSATE RESUSPENSION, AND SLOPE/SHELF WATER INTRUSIONS by Marshall H. Orr and Frederick R. Hess. Reprinted from "Journal of Geophysical Research, Vol. 83, No. C8, August 20, 1978, pp. 4062-4068". October 1978. Prepared for the Naval Oceanic Research and Development Activity under Contract N00014-77-C-0196.</p> <p>Acoustic data, transmissometer data, and calculations are presented which indicate that high-frequency acoustic backscattering systems can become a valuable tool in the remote monitoring of suspended particle distributions and active resuspension areas. Data are also presented which show that acoustic backscattering systems can be used to remotely detect slope/shelf water frontal zones. Towed acoustic systems should be able to map the extent of the frontal zone and add significantly to the understanding of frontal zone processes.</p>	<p>1. Acoustics</p> <p>2. Physical oceanography</p> <p>3. Particulate distributions</p> <p>I. Orr, Marshall H.</p> <p>II. Hess, Frederick R.</p> <p>III. N00014-77-C-0196</p> <p>This card is UNCLASSIFIED</p>	<p>Woods Hole Oceanographic Institution WHOI-78-70</p> <p>REMOTE ACOUSTIC MONITORING OF NATURAL SUSPENSATE DISTRIBUTIONS, ACTIVE SUSPENSATE RESUSPENSION, AND SLOPE/SHELF WATER INTRUSIONS by Marshall H. Orr and Frederick R. Hess. Reprinted from "Journal of Geophysical Research, Vol. 83, No. C8, August 20, 1978, pp. 4062-4068". October 1978. Prepared for the Naval Oceanic Research and Development Activity under Contract N00014-77-C-0196.</p> <p>Acoustic data, transmissometer data, and calculations are presented which indicate that high-frequency acoustic backscattering systems can become a valuable tool in the remote monitoring of suspended particle distributions and active resuspension areas. Data are also presented which show that acoustic backscattering systems can be used to remotely detect slope/shelf water frontal zones. Towed acoustic systems should be able to map the extent of the frontal zone and add significantly to the understanding of frontal zone processes.</p>	<p>1. Acoustics</p> <p>2. Physical oceanography</p> <p>3. Particulate distributions</p> <p>I. Orr, Marshall H.</p> <p>II. Hess, Frederick R.</p> <p>III. N00014-77-C-0196</p> <p>This card is UNCLASSIFIED</p>