AD-816 404 L

67-23
Copy 1

WOODS HOLE OCEANOGRAPHIC INSTITUTION

REFERENCE NO. 67-23

DEEP SUBMERGENCE RESEARCH CONDUCTED DURING
THE PERIOD 1 JANUARY THROUGH 31 DECEMBER 1966

*Each transmittal of this document outside of
the agencies of the U.S. Government must have
prior approval of the Office of Naval Research,
Boston Branch.*

WOODS HOLE, MASSACHUSETTS

WOODS HOLE OCEANOGRAPHIC INSTITUTION
Woods Hole, Massachusetts

REFERENCE NO. 67-23

DEEP SUBMERGENCE RESEARCH CONDUCTED DURING THE PERIOD
1 JANUARY THROUGH 31 DECEMBER 1966

April 1967

TECHNICAL REPORT

*Submitted to the Office of Naval Research
under Contract Nonr-3484(00) NR 260-107.*

*Reproduction in whole or in part is permitted
for any purpose of the United States Government.
In citing this manuscript in a bibliography, the
reference should be followed by the phrase:
UNPUBLISHED MANUSCRIPT.*

*Each transmittal of this document outside of
the agencies of the U.S. Government must have
prior approval of the Office of Naval Research,
Boston Branch.*

MBL/WHOI

0 0301 0033298 7

Approved for Distribution

Earl E. Hays

Dr. Earl E. Hays, Chairman
Department of Applied Oceanography

TABLE OF CONTENTS

Page No.

Abstract	i
Reports, Papers and Articles	ii
Introduction	1
The Aircraft Salvage Operation, Mediterranean	5
Overhaul Completion of DSRVT-1	13
Instrumentation	13
ALVIN Refit May - June 1966	13
Bermuda Expedition	14
AUTEC Operations	15
Movies and Science	16
NAVOCEANO Dive Series	16
Operations off New England	17
New Construction	17
Structural Design	18
Research Submersibles Workshop	18
Outside Assistance	20
Personnel	20
Future Program	21
Illustrations	23
Appendix A - Summary of Modifications	A1
Appendix B - Preparations for Shipment	B1
Appendix C - Deep Submergence Research Vehicle ALVIN Dive Summary	C1
Appendix D - Summary of Dives	D1
Appendix E - Summary of NAVOCEANO Dives in TOTO	E1

Abstract

Deep Submergence Research

1 January through 31 December 1966

The Deep Submergence Research Program at Woods Hole Oceanographic Institution (WHOI) entered into the first full operational year during 1966. ALVIN and the support catamaran underwent modification and overhaul during the winter months.

ALVIN played a key role in the successful recovery of an H-Bomb lost in the sea off Palomares, Spain. This operation is reported in some detail. ALVIN then embarked on a series of dives supported by the catamaran. One series off Bermuda was to inspect the ARTEMIS array. Transit was then made to Tongue-of-the-Ocean (TOTØ) in the Bahamas. There portions of the AUTECH range were inspected, several WHOI science dives were made, and a diving program carried out for the Naval Oceanographic Office (NAVOCEANO).

After tow back to Woods Hole, two science dives were made and both ALVIN and the catamaran went into an extensive refit and inspection period. The plans for this activity are reported in some detail.

A new ALVIN-type submersible is under design and construction at Electric Boat Division of General Dynamics Corporation.

Reports, Papers and Articles

The following technical reports, papers and articles contain detailed information developed under this contract during the report period:

1. WHOI Reference No. 65-52 "Observation Windows of the Deep Submersible, ALVIN", by J. W. Mavor, Jr., dated December 1965 (printed in March 1966).
2. WHOI Reference No. 66-22 "Deep Submergence Research Conducted During the Period 1 January through 31 December 1965" dated June 1966.
3. "Ten Months with ALVIN" by J. W. Mavor, Jr., in Geo Marine Technology, Vol. 2 No.2; February 1966.
4. Letter Report on Inspection and Overhaul of ALVIN, November 1965 - January 1966 dated March 14, 1966.
5. WHOI Technical Memorandum No. DS-21 "Long Term Exposure and Cycling Tests of Syntactic Foam Buoyancy Material Used in DSRV ALVIN", by W. S. Shultz and F. P. Omohundro. June 1966.
6. WHOI Technical Memorandum No. DS-22 "A Discussion of Various Means for Improving Visibility from the DSRV ALVIN or Similar Vehicles", by Lincoln Baxter, II. November 1966.
7. ALVIN and the Bomb by W. O. Rainnie, Jr., in OCEANUS Vol. XII. No. 4 August 1966.
8. ALVIN, 6000-Ft. Submergence Research Vehicle, by J. W. Mavor, Jr., Harold E. Froehlich, William M. Marquet and W. O. Rainnie, Jr. A paper presented at the Annual Meeting of The Society of Naval Architects and Marine Engineers on November 10, 1966. (In print in the transactions.)
9. Letter Report on Inspection and Repairs of DSRV ALVIN, May-June 1966 dated July 14, 1966.
10. Comparison Tests of Epoxy Potted and Sand Filled "Amp-trap" 150 ampere Fuses, preliminary report by W. S. Shultz dated July 1966.
11. Inspection of the ARTEMIS Array (U), by W. O. Rainnie, Jr. dated November 25, 1967 presented at the Underwater Acoustic Symposium on December 1, 1966. CONFIDENTIAL (In print in the Transactions.)
12. Hydrostatic Tests of a 6 AL - 4V Titanium Buoyancy Sphere for ALVIN, by P. E. Humphries, David Taylor Model Basin dated January, 1967.

Introduction

This year, 1966, may become known in subsequent history as the one in which deep submergence vehicles (DSV) "came of age." Up until this point in time, it was necessary for proponents of DSRV's to project their capabilities with a great deal of imagination and speculation. This year a growing number of DSRV's participated in research and other dives worthy of world-wide attention. No longer is it necessary to speculate whether the DSRV's can perform useful and valuable work because they have already done so.

It started in January with the call from the Navy for the ALVIN, ALUMINAUT and CUBMARINE to assist in the search for a Hydrogen Bomb lost in an unfortunate collision between a B-52 Bomber and KC135 tanker over Palomares, Spain. These three vehicles plus the unmanned CURV (Cable-controlled Underwater Recovery Vehicle) played a major role in the operation that succeeded in finding the lost weapon and its recovery - a major achievement in protecting the security of the U.S. and the free world.

ALVIN went on from there to inspect a major portion of the ARTEMIS array off Bermuda, the Atlantic Underwater Test and Evaluation Center (AUTEC) range in the Bahamas and also to perform a variety of special experiments for the Naval Oceanographic Office (NAVOCEANO). Sandwiched in between were several WHOI scientific dives. One off Bermuda for biology, three (3) in Tongue of the Ocean (TOTO) for geology, and one into Oceanographer's Canyon, the first time a geologist has looked directly into one of these major features of the Atlantic slope.

ALUMINAUT also has been busy, having recovered a ton of oceanographic instruments from deep water in the Caribbean as well as bringing back a large sample of manganese from the Blake Plateau.

CUBMARINE and ASHERAH were called on again to assist in finding a lost device near Vieques in the Caribbean. On the Pacific Coast, Westinghouse's DEEPSTAR 4000 was christened and commenced a series of successful scientific dives with Scripps Institution of Oceanography (SIO) and the Naval Electronics Laboratory (NEL) observers. Electric Boat's (EB) STAR II and STAR III were launched this year and commenced a series of successful dives on various projects.

The Deep Submergence Systems Project (DSSP) program took a step forward with the award of a contract to Lockheed for the Deep Submergence Rescue Vehicle. Lockheed was already busy on its own DEEP QUEST due for launching in 1967. General Motors started construction of the DOWB, and Ocean Systems on a submarine with diver lockout capability with Perry Submarine Builders, Edwin Link supervising the design. All three of these mentioned vehicles will be operational by mid-1967. The contract was awarded to EB for two more ALVIN-type vehicles this year for delivery in early 1968.

Thus many newcomers are now joining the growing fleet of deep diving submarines.

Although the number of submersibles grows daily, the surface support ship development lags rather badly. There is still a limitation on operations of all of the DSV's whenever the wind blows over 15 knots or the seas get more than 5 feet in height. Underwater tracking and navigation is still relatively crude. The catamaran developed by WHOI continues to be the most advanced surface support and DSV tracking ship, built for that purpose, but it is still in the developmental stage and is an early prototype. Lockheed is building a ship called SUBPORTER that should be operational soon.

At the end of this report period negotiations were being conducted between WHOI and NAVOCEANO to make a major step forward in underwater navigation and other instrumentation. Very little progress seemed to be imminent in the surface support ship field. It is hoped that the extensive DSSP effort on these problems will begin to pay-off in the near future.

General

ALVIN was at Otis Air Force Base finishing an annual inspection and refit (see page 11 of Report No. 2 for major items accomplished, with details contained in Report No. 4.) preparing for departure for Tongue of the Ocean and a test diving program to see if the technical problems uncovered in the 1965 dive series had really been corrected. The call from the Office of Naval Research (ONR) came on January 22nd, and ALVIN with full support equipment was loaded onto two Air Force Cargo Planes by 1 February enroute to Rota, Spain to participate in the H-bomb search off Palomares. (See Figure 1) Final assembly and a shallow test dive were conducted at Rota and the submarine, crew and equipment were loaded on the USS PLYMOUTH ROCK (LSD 28). The ALUMINAUT was already embarked. Both were then transported to Palomares. There, plans were carried out to transfer to USS FORT SNELLING (LSD 30) that was to become our support ship for the operation. After a bad storm delayed the transfer, the first dive was made from FORT SNELLING on Valentines Day. This commenced a series of some 34 dives in the search and finally successful recovery of the missing bomb on April 7th. This operation was an important event in the development of ocean engineering in general and deep submersibles in particular. It was the first recovery of a valuable piece of equipment from water deeper than 2,000 feet. But probably more important was the fact that finding it in the first place was believed by most to be practically impossible.

ALVIN was transferred to USS LINDENWALD (LSD 6) for one dive and then transported to Woods Hole, air transportation not being considered as desirable after the urgency was removed.

ALVIN was transferred to the USS SAN MARCOS in Little Creek for the final leg to Boston where it was picked up on May 5th by the DSRVT-1 LULU on her maiden sea voyage after a major modification during the winter, 1965-66.

The catamaran modification and maintenance program was the one described in Report No. 2, page 14 completed by March 1966.

After a refit period in Woods Hole to replace batteries and make other minor repairs and inspections to ALVIN. The catamaran with ALVIN embarked, departed Woods Hole under its own power on 24 June in company with M/V NARRAGANSETT as escort, bound for Bermuda. Upon arrival, a series of dives was conducted to inspect the ARTEMIS array off Plantagenet Bank. One biology dive 5850' with Robert Hessler was conducted not far from the area that Otis Barton and William Beebe dove in more than 30 years earlier in the "Bathysphere."

A Navy tug, USS KEYWADIN, took the DSRVT-1 in tow for the Bahamas, arriving there on July 28th. A series of dives for the Atlantic Underwater Test and Evaluation Center (AUTEC) were made to inspect the terrain and underwater arrays. Then a short series of shallow dives were made to take underwater movies for a film produced for the National Education Television Network. (It is being shown nationwide on NET stations during December and January).

Allyn Vine made his first deep dive in ALVIN followed by John Schlee to look at the geology of TOTO south of Goulding Cay.

In late August a month-long series of 15 dives were made for the NAVOCEANO under the supervision of Mr. R. Frank Busby to evaluate the usefulness of DSRV's for deep ocean survey work. An interesting series of experiments were conducted to investigate such things as underwater visibility, soil mechanics, biological fouling, marine geology including samples, sub-bottom profiling, bottom acoustic reflection loss, gravity measurements, bottom site-survey, and sub-surface navigation systems.

The catamaran was then towed to Woods Hole by the USS ACCOKEEK, arriving on October 2nd. One more series of dives were attempted. This resulted in one dive east of Cape Cod to observe the micro-structure of the thermocline by Claes Rooth. One dive was made into Oceanographer's Canyon by James Trumbull to investigate the geology of continental slope canyons. Additional dives planned there were cancelled because of weather and the annual refit was commenced on 21 October. The refit is still in progress at the end of this report period. Major modifications to ALVIN and the DSRVT-1 are being undertaken. Major items for ALVIN include:

- 1) Replace aluminum spheres with titanium spheres.
- 2) Rearrange the internal personnel sphere.
- 3) Add additional buoyancy (syntactic foam) for more payload.
- 4) Replace wiring.
- 5) Inspect and repair the aluminum frame.
- 6) Replace ball valves with solenoid valves in the main ballast and variable ballast systems.
- 7) Replace batteries with longer lived ones and add some additional capacity.
- 8) Improve photography capability.
- 9) Inspect all parts for wear and recondition.
- 10) Replace the outer fairing.
- 11) Improve the external lighting.

Major items for the catamaran include:

- 1) Remove the Holly hoist and utility van to save weight and to improve the capability.
- 2) Replace these items with "built in" facilities which are lighter and more efficient.
- 3) Improve surface navigation and underwater tracking capability.
- 4) Overhaul engines and generators.
- 5) Add hydraulic system for steering, main hoist system, anchor windlass and sub-tracking tower.
- 6) Improve unsatisfactory air conditioning.
- 7) Provide additional bunks.
- 8) Install adequate darkroom facilities and wet-lab space.
- 9) Inspect and repair all equipment. Rearrange bridge in accordance with experience from operations.
- 10) Cut-out unnecessary structure, etc., in order to increase fuel carrying capacity and provide improved trim and list control.

For more complete description of these modifications. See Appendix A.

The Aircraft Salvage Operation, Mediterranean (AIR SALVOPS MED)

Preparations for Shipment - The details, for future reference, are described in Appendix B.

Assembly and Test at Rota, Spain

The C141 departed Otis AFB 1 February and arrived in Rota 2 February. The C133 (See Figure No.1) did not get off until 2 February because of weather, and arrived Rota 5 February. The submarine was assembled and check-outs performed for a dive on February 7th. When about 3/4 submerged, large grounds were detected on the control circuits and the control circuit fuse in number 3 battery blew aborting the dive prior to full submergence.

After the batteries were removed, the trouble was discovered to be water leakage into the tops of the batteries through the connector plates. It is believed these worked loose from vibration of the airplane, which was severe at times on the way over to Spain. These were repaired and another test dive conducted in Rota harbor on 9 February. This was successful and the submarine and support equipment was loaded onto USS PLYMOUTH ROCK (LSD 29) that afternoon for transport to the search area off Palomares in the Mediterranean. ALUMINAUT was already on board having been brought across the Atlantic from Miami, Florida.

Operations at Palomares

a. Arrival

Upon arrival it was learned that a transfer to USS FORT SNELLING (LSD 30), (Figure No.2), was required since PLYMOUTH ROCK was returning to CONUS. ALVIN and ALUMINAUT were moored to buoys on the 11th so the loads could be transferred between LSD's while moored. A "mistral" came up suddenly with winds of over 70 knots and it was 21 hours later before ALVIN was back in the well of PLYMOUTH ROCK. The submarine suffered minor damage to the skin on the afterbody (which also holds the lift props on!) that took two more days to repair. Then the transfer by LCU from PLYMOUTH ROCK to FORT SNELLING was made. The first dive in the search area was made on February 14 from FORT SNELLING to a depth of 1800'. ALVIN had been assigned the high probability area, a 1,000 yard circle south and east of the fisherman's position that was to remain the general area of search for the remainder of the operation except for two dives in 500-800 feet of water later in March.

b. It should be mentioned that a great deal of "behind-the-scenes" activity went on during this period. Besides transferring all equipment from one LSD to the other and setting up the shops and chargers for operation, the procedure for launch and recovery was worked out with both LSD's. The fact that no

trouble was experienced with this part of the operation attests to the good seamanship and skill on the part of the PLYMOUTH ROCK, FORT SNELLING and the ALVIN crew. In addition, the portable UQC and tracking gear had to be put on an MSO, the SKILL (MSO 471), (Figure No.4), and procedures for tracking worked out with that vessel as well as the USNS MIZAR (Figure No.5) This part of the operation also became routine in a short time and later proved successful.

c. Operating Schedules

After an unprecedented five consecutive days of diving (it was anticipated and announced we would be able to dive only every other day), a four day diving and one day down schedule was agreed upon in order to equalize the batteries. When necessary later in the recovery phase, this schedule was ignored and ALVIN made 11 dives in 12 days.

Unfortunately ALUMINAUT's support and ALVIN's operations from the LSD were in direct conflict when ALUMINAUT required docking for upkeep or repairs. Over-the-side launch and recovery of ALVIN was made on two occasions but this method was dangerous for both the operators and the submarine and was not used after one particularly bad experience, which fortunately ended without serious damage.

d. Launch and Recovery

ALVIN's normal launch was from the flight deck into a flooded well (8 1/2 - 9 feet water depth under the crane). Four or six tending lines were used until clear of the well. ALVIN drove under power to the stern gate, which was then opened and ALVIN drove clear. The tending lines were recovered by rubber boat and swimmers. After some experimentation with towing ALVIN by motor whaleboat (MWB) more closely to the preferred diving point, it was found that it was usually better to dive where launched if reasonably close to the dive point (within 1000 yards).

The recovery of ALVIN was essentially the reverse of the launch except the MWB was used to tow ALVIN astern of the LSD from the surfacing point. An inhaul line from the LSD was then attached by rubber boat to the towing bridle of ALVIN and the MWB cast off. When hauled close enough to the stern of the LSD, swimmers attached the tending lines and ALVIN drove forward (Figure No. to the crane and was then lifted up to the flight deck. The ballast was then pumped until the well was dry. On some occasions ALVIN was launched and placed back on the well-deck instead of to and from the flight deck. It was satisfactory this way as battery and air charging cables were long enough to reach; however, it was quite a bit easier to service the submarine on the flight deck next to the support vans than in the well. This was the method generally used.

The crane of the LSD was used in either case because it was found that the waves in the well, even with the stern gate closed, were large enough to prevent sitting down solidly on ALVIN's skids immediately. This caused pounding on the submarine skids that was undesirable. Since the crane was available, it was used on all launches and recoveries after the first one in PLYMOUTH ROCK.

e. Tracking Systems

Tracking from the MSO's was crude at best with the portable equipment provided by WHOI. UQC ranges, rough depth contours, and approximate bearings on UQC transmissions using a line hydrophone hung over the side of the MSO was the method employed. Instead of ± 200 yard accuracy expected, it was only good to approximately ± 400 yards in the depth of water ($> 2000'$). Nevertheless it was the system that first found the bomb in 2,500 feet of water. MIZAR's Underwater Tracking Equipment (UTE) was then used (± 140 feet) to return to the bomb on the bottom each time it was attempted. Pilot familiarity with the bottom terrain was a vital part of this system however, as the MIZAR's UTE was not good enough to direct ALVIN to within visual contact of the point. No system good enough to do a 100% search of the 1,000 yard squares laid out for search patterns. "Fortune Cookies" were made and available but were not used for several reasons. One reason was that they would present numerous false targets for search sonars; and two, they had to be in close proximity to each other (less than 40 feet) in order to acquire one from another one visually. This required a very large number to mark the areas of greatest interest.

It should be stated unequivocally that without the DECCA network in operation for surface ship navigation, the search and recovery would have been many times more difficult, if not impossible. Although it failed on some occasions (wind storms usually) and required daily reference checks by ships using it, it was more reliable during our presence than most electronic systems. Search operations were not interrupted by DECCA failures nearly as often as by weather.

Another lesson of value is that the conn of the ship, the plot of the track (Ship and DSRV), and the DSRV surface controller must be in close physical proximity in order to function well. This is not a new discovery, just a reaffirmation of operating procedures for similar missions (i.e. combat air patrol control from CIC). An important consideration is position of the ship relative to the DSRV and the bottom terrain. Sound (communications, tracking equipment, etc.) does not travel behind hills very well. It is usually better to remain "down-slope" from the submersible. This and any physical limitations such as location of the sound gear, acoustic interference from propulsion, etc., should be clearly explained to commanding officers and conning officers.

CIC conn (where the plot is maintained) with the bridge serving only as a lookout and safety control station worked very well both on the MSO's and MIZAR.

f. The First Search Phase

ALVIN arrived in Spain essentially untested after an extensive overhaul. The shallow test dive in Rota harbor was reassuring, but not conclusive. Therefore the pilots dove the submarine on the first two deep dives, and then after observing the terrain, (See Figure No.6), the currents, etc., it was decided that a third person in the sphere would be a very important addition to increase the search capability. Thus almost all dives in the search phase made without the mechanical arm were with two pilots and one observer. The mechanical arm arrived by air in the middle of February, having recently been repaired. In order to test it in deep water, two dives were made with it mounted and without an observer, since the arm weight is such that with it mounted the reserve buoyancy remaining in the variable ballast system is lower than desired. A general policy has been adopted that when the arm is mounted, only two persons are in the sphere.

ALVIN was first assigned the task of classifying targets in a semicircle of a thousand yard radius southeast of the reported impact position by the Spanish fisherman, Simo Orts. This was considered one of two high priority search areas, the other being the computed splash point. The latter area was on leveler bottom to the northwest and was a more suitable area for ALUMINAUT, where it was assigned. ALVIN's search dives turned up various artifacts on the bottom including one piece of aircraft wreckage. However, correlation of the side-looking sonar contacts and the visual ALVIN contacts was not satisfactory because of the uncertainties of the navigation errors in the submarine tracking system, and in the side-looking sonar position when contacts were observed on that equipment in deeper water.

A review of the dive summary Appendix C will reconstruct the sequence of dives during the search phase prior to discovery of the weapon on Dive No. 128 (Local Dive No. 19) March 15th. The things that led to the discovery of the weapon were a series of assumptions based on reported information and on-the-scene observation. These were:

- (1) Assumption that fisherman's reported event was fact and that his reported position was accurate. First of all the land terrain (mountainous) and bottom terrain (he had an echo sounder) were conducive to visual (eyeball) navigation. He was intimately familiar with the area having earned a good living fishing there for many years. (It was accurate.)

(2) The observed deeper (below 1,000 feet) current direction and average force. This was generally down-slope to the southwest and varied between zero and occasionally exceeded 1 knot. The surface current varied much more in force and direction. (The bomb actually had dragged down-slope on a general heading of 240°.)

(3) Observation of the bottom terrain. It sloped sharply to the south of the position of the highest probability (also the general direction of major deeper currents).

(4) Assumption that the 'chute was deployed as reported by Orts and remained so to the bottom. This led to the supposition that the weapon should leave a track on the bottom for some distance because of the parachute drag in the current and particularly if it landed on the steeper slopes observed. (Note - ALVIN pilots and observers started looking for the track on the second dive.) It was believed that the track should be recognizable and different from the many other tracks observed on the bottom in this area made by fishing gear.

(5) Assumption that weapon and 'chute remained together as reported by Orts. He said it sank too quickly for him to recover the "half man" attached. If the weapon had not remained attached, the 'chute probably would have been recovered. Here, it must be admitted that we did not ignore unusual depressions and mounds whenever discovered in the event they had become separated. However, this assumption led us to believe we were looking for a much larger target than if the weapon were not attached to the chute. This was the case.

In summary, the result of these assumptions and observations led us to believe the weapon and 'chute were attached and a distinctive bottom track would make a larger search target. We firmly believed from the beginning that the weapon would be found downslope from the fisherman's position to the south. Depending on how long the 'chute took to reach the bottom, we believed it would be found at the bottom of the canyon where the current became very much less. This latter supposition was in error as it did not reach the very bottom, but all of the other deductions were basically correct and led to the discovery. These comments are entered into this report because the rationale developed was of major importance in sustaining real hope of success and kept morale high. It was believed we were operating in the area where it would be found on all but two dives, No.'s 124 and 124, in shallower water.

The reasons it took so much longer to find the weapon than might be expected was due partly to the errors in tracking the submarine on the bottom from the surface. Even though MIZAR was the tracking ship on the first track discovery on March 1st, her navigation system at that point had unknown but suspected errors in it that were fortunately isolated and corrected by MIZAR prior to the discovery of the weapon. For example, it was believed that ALVIN was in the southwest corner of the 1000 x 1000 yard square, C-4, the first time. When the bomb was actually found it was in the southeast corner of C-4 about 800 yards away. These uncertainties and the reluctance of the staff to believe that the track was the real thing were the major cause of delay. An interesting coincidence occurred on the dive that first discovered the track. Captain Frank Andrews, the Task Group Commander during the THRESHER search, was the observer. He too believed that the track was of uncommon interest.

The terrain also contributed to the delay in finding the weapon. The slope was very steep at the point where it finally hung up and was found (See Figure No.6). On the first two track-following dives, the submarine apparently passed very close to the weapon without sighting it, because the bottom fell away so sharply the track could not be followed visually and was lost. On the third dive on the track, McCamis and Wilson very wisely (and bravely) backed down the slope to keep the track in sight, and thereby discovered the parachute-shrouded weapon in 2550' of water. Photos were taken (Figure No.7), and analyzed as not positive immediately because so much of the actual weapon was covered by the 'chute. However, the portion of the aircraft bomb rack was exposed and led to eventual identification. Location of the cameras high on the nose of ALVIN did not permit photos of the same things that the pilots could see through the viewports. Thus at first their belief that they had found the weapon was not fully shared by Admiral Guest (CTF 65).

The First Recovery Attempt

ALUMINAUT was instructed to rendezvous (the first one in deep "inner space") with ALVIN when the weapon was found in order to pinpoint the target using the best tracking system available - MIZAR's UTE. ALVIN was being tracked by USS ABILITY (MSO 519) when the weapon was found and was not carrying a MIZAR transponder. ALUMINAUT took a MIZAR transponder on board and by a combination of surface vectoring and FM Sonar contact between submarines, landed within visual distance of ALVIN at the scene. ALUMINAUT remained there for 22 hours while MIZAR accurately fixed the position. Meanwhile, ALVIN surfaced to charge batteries, mount the mechanical arm and plan the next step. The unexpected discovery caused a great deal of debate as to the next step. The next four dives were made in the first attempt to raise the weapon. A basic consideration in this series of dives was to plant an anchor or some other object with lift line attached on the bottom near the target. From this a similar large line could be attached to the weapon

by ALVIN without the impediment of the surface tended lift line which was being pulled about by currents, surface waves and surface tending ships. At this point the target was in a very precarious position conducive to slipping further down the steep slope. The special features of each dive in summary is shown in Appendix D.

The Second Search Phase

After the line broke, ALVIN had a mercury system leak which was repaired and dove late in the day. ALUMINAUT was sent down in the interim to search for the dropped weapon. This dive was unsuccessful. ALVIN was likewise unsuccessful in locating a track or the weapon because of low visibility caused by the lift attempt and ALUMINAUT. ALUMINAUT tracks misled ALVIN it is believed. No pinger or transponder signals were discovered by either submersible.

The search continued for a short period without success. ALVIN then changed Straza Sonars in one day in order to acquire a transponder mode not included in the original set and to improve marginal operation experienced up to that time. The full search pattern of two pilots and an observer was reinstituted and the mechanical arm was taken off.

Much of the search was concentrated to the north because the bottom evidence from the original resting position of the weapon seem to indicate it had been dragged up the slope, lifted off and fallen on the flatter terrain above 2,000 feet. "Lift-off" was at 2100'.

After doing a fairly fine-grained search above the original site, the ALVIN Group prevailed upon the staff to search below and on Dive No. 140, April 2nd, the weapon was again found almost due south of the original resting place in 2800' of water. This time it was in a less precarious position. On this dive it was again a coincidence that Lcdr. George Martin, pilot of TRIESTE on THRESHER search, was the observer. The weapon was now wrapped in the 'chute completely. It apparently had slid down the same track as it went up on the lift attempt, and this obscured the subsequent course of events. This was further complicated by a profusion of ALUMINAUT tracks in the near vicinity. Again ALUMINAUT and ALVIN relieved each other on station.

By this time CURV (Controlled Underwater Recovery Vehicle), (Figure No. 9), from NOTS, China Lake, had arrived on the scene and had been modified and tested for 2800' depth operation.

Conclusion of the Operation

ALVIN made three more dives to reconnoiter, plant 37 KC pingers, a 45 KCS pinger for the CURV homing, and an attempt to untangle the parachute to identify that the weapon was still attached. CURV attached a line to the 'chute at the crown after ALVIN spread it out. This line was then buoyed off. ALVIN reluctantly made a dive to see what had resulted from putting a strain on this line by small boat in

an attempt to unravel the 'chute. The weapon had been moved several hundred feet away and in tracking it down hill, ALVIN almost got entangled in the billowing 'chute (billowing because of the bobbing buoy on the surface). CURV then went down again, assisted by ALVIN pilot Wilson, and attached another line. On the next try to attach the 3rd line, CURV got hopelessly entangled in the 'chute and the bomb was lifted, CURV and all, by PETREL on April 7th. ALVIN was submerged during the lift to track the pingers to the surface from about 1,000 yards away. This was done in the event it was dropped again. Fortunately this was a successful lift and the difficult job was done at last. (Figure No. 8) The DSRVG personnel then left Palomares and returned home by air, leaving one person to accompany ALVIN back to the U.S. on USS LINDENWALD (LSD 6).

By the end of the operation ALVIN had made 34 dives, for a total of 223 hours submerged and had contributed significantly to the overall success of the search and recovery of our first H-bomb lost in international waters. ALVIN and the support group had been previously transferred from FORT SNELLING to USS LINDENWALD on April 6 for the final dive and transport home.

Radioactive Monitoring

Dr. Hays borrowed a radiation measuring device from another project at WHOI that was used to test bottom samples from the skids of ALVIN after each dive. The data taken indicated that no significant radiation existed on the bottom from the weapon at any time. A known sample of radioactive material was used to test the counter prior to measuring the samples to insure that the readings were meaningful. Wrist watches were several orders of magnitude more "radioactive" than any of the bottom samples measured.

WHOI Personnel Actively Participating

Dr. Earl E. Hays, William O. Rainnie, Marvin J. McCamis, Valentine P. Wilson, William M. Marquet, George deP. Broderson, Arthur C. Bartlett, Mark P. Fox, Russell G. Graham, David H. Mason and Chester R. Porembski were participants. Frank P. Omohundro joined ALVIN briefly at the end of the operation. George Broderson rejoined the LINDENWALD after hospitalization to accompany the ALVIN back to the U. S. Oceanographer John Bruce was also present to advise the staff on underwater currents, etc.

Cdr. Rhodes Boykin from Code 466 ONR was present throughout the operation and rendered invaluable liaison with the Task Force Commander and staff. He also rendered much needed assistance in the surface control party as well as acting as an observer on several key dives. Lcdr. George Brown also joined later and was very helpful in the many administrative details of this operation.

Return to the U. S.

The operating and support crew of the ALVIN vehicle returned to Woods Hole from Palomares, Spain, with the exception of George Broderon who was assigned to accompany the ALVIN, embarked on the USS LINDENWALD (LSD 6) for return to the United States. The catamaran and crew were in Woods Hole continuing preparations for the summer diving schedule interrupted by the Spanish expedition. ALVIN returned from Norfolk to Boston on 5 May aboard USS SAN MARCOS having been transferred from LINDENWALD, which had experienced a boiler casualty on the Atlantic crossing. As a result of the rigors of the diving schedule in Spain, the ALVIN was partially disassembled and refitted prior to deployment from Woods Hole on June 24 enroute to Bermuda. (See Report No. 9)

Overhaul Completion of DSRVT-1 (Figure No. 10)

The completion of painting, loading of equipment, stores and provisions, overhaul of the submarine lifting system and test of same, installation and test of a new battery handling system, constituted the major part of the work accomplished to complete the overhaul done in Munro's Shipyard, Boston, during December and January. The catamaran departed for Boston under command of Captain Allan Davison, to pick up ALVIN. It returned to Woods Hole, the first extensive sea voyage for this unique vessel under its own power. See Appendix A for details of work done.

Instrumentation

Work was continued on instrumentation in a limited way because of budget restrictions. A "precision time" navigation system was designed and built by the WHOI electronics shop for use with the Submarine and ALVIN for tracking purposes during dives off Argus Island. This system was a "breadboard" model and met with only limited success believed to have been related to instability of the trigger circuitry. This system was improved and used later in the Bahamas with much better results. As mentioned, the CTFM Sonar was replaced twice; once in Spain and finally during this period.

ALVIN Refit May - June 1966

ALVIN was partially disassembled on the catamaran during this period to accomplish the following major items:

- a. Replace batteries
- b. Inspect variable ballast spheres
- c. Replace mercury fitting
- d. Repair leak in Main Ballast Tanks
- e. Remove and replace loaned Straza CTFM Sonar
- f. Install new vent valves in Main Ballast System

A post-refit shallow test dive was conducted in Woods Hole Harbor.

Bermuda Expedition

Catamaran Transit to Bermuda

The catamaran proceeded to Bermuda under its own power. However, it was necessary to refuel from escorting M/V NARRAGANSETT enroute. Arrival in Bermuda was delayed by weather, but all gear and machinery worked well. During the latter part of this voyage waves up to 20 feet in height were encountered without undue difficulty; however speed of advance was reduced at times to almost zero. A single side-band radio was loaned by USNUSL, New London and provided long-range communication throughout the voyage between the catamaran, USNUSL and Tudor Hill Laboratory. Some problems were encountered with this radio due to antenna mismatch. This was corrected in Bermuda by the Research Detachment. Additional radio equipment was also installed to provide short range communications with Tudor Hill and Argus Island.

The catamaran arrived in Bermuda with foul weather and therefore diving at Argus was delayed. A shallow test dive was conducted in the harbor at the Naval Base to check out the systems, especially the sonar, on July 1. In tow of YTM 176, the catamaran deployed to Argus Island on July 2nd and commenced diving on the 3rd. A series of three dives were completed inspecting about one third of the 1961 horizontal string, a part of String No. 10 (1963) and most of String No. 9. Hurricane warnings forced evacuation of Argus Island and the catamaran returned to port under tow of YTM 176. The Straza Sonar was not working on the first dive, so the Straza Technical Representative was called to Bermuda to repair it. In addition, the WHOI designed and built "real time" pinger system was installed and tested by WHOI personnel. The results were marginal because all of the deficiencies had not yet been taken care of. Work continued at WHOI on this system for test in the Bahamas. After the weather passed, the catamaran returned to Argus Island, in tow of YTM 176, and completed three more dives to inspect Strings Nos. 7, 6 and 5, returning to port because of weather on July 13th.

Weather kept operations suspended until July 17th, at which time the first deep science dive of ALVIN was made on the way to Argus. Dr. Robert Hessler, a WHOI biologist, was the observer and Marvin McCamis the pilot. (This was also the first deep dive with one pilot and one scientific observer.) Two plankton sampling nets were rigged on ALVIN, to be selectively opened and closed by the mechanical arm. These were used to collect samples very near the bottom interface, a task very difficult to accomplish from a surface towed net. Samples were obtained and are being analyzed. Better plans for future deep biology dives resulted from this one. Dr. Hessler was transported ashore by Boston Whaler upon completion of his dive and the catamaran proceeded to Argus.

On July 18th, the final dive in the Bermuda area was made with Mr. Donn Cobb of the USNUSL Research Detachment as observer to inspect the 1963 String No. 1, and portions of the 1961 vertical string which was located just to the west. (Note: A more complete report of this series of dives on Plantagenet Bank was made in a paper presented at the Navy Underwater Acoustic Symposium, December 1. It is classified CONFIDENTIAL and will be published in the proceedings of the Symposium).

Summarizing the ARTEMIS dives, seven were made in total. 103 of the 209 (one was found missing) modules were inspected. ALVIN's observations confirmed suspected problems and revealed some new ones. This was the deepest (6000') known underwater inspection and photographic mission done to date, and it was done in the unfriendliest of terrains. Cliffs, gullies, and strong currents (up to an estimated 2.0 knots) were encountered. It did, however, fulfill a commitment made when the ALVIN concept was first suggested in 1962 which resulted in the construction of the vehicle and its support craft.

The catamaran returned to St. Georges on July 19th to await the arrival of USS KEWAYDIN (ATA 213). It arrived on 21 July, one day late because of the tail-end of hurricane Dorothy. Departure for Andros Island, Bahamas was delayed by the same storm until 23 July. The tow then commenced, arriving AUTECH, Andros Island on July 27th. Maintenance was conducted on ALVIN enroute to correct small saltwater leakage into the Main Ballast valve box.

It should be noted at this point that complete logistic support and fullest cooperation in solving problems were provided by the Tudor Hill Laboratory (Cdr. Joseph Pinning) and the Bermuda Naval Station (Captain Dawkins) to the ALVIN Group. The YTM 176, provided by the Naval Station, was especially helpful in the execution of our mission there. Enough cannot really be said about the support and assistance we received from all elements of the Bermuda complex, both civilian and military.

AUTECH Operations

Upon arrival, all of the DSRVG logistics requirements were taken care of by AUTECH, at Site No. 1, the main base. A meeting was held with the Commanding Officer, Cdr. Glen Barney and his staff and a diving program was developed to be completed in a two week period. Commencing July 29, a total of eight dives were completed in direct support of AUTECH. These were completed on August 12th. In summary, these dives were made to inspect underwater hydrophone emplantments, the cable runs and in one instance to inspect a large vertical acoustic array. All dives, but one, accomplished their goal. One hydrophone bail, used to plant the hydrophone, was found to be upright instead of down as designed. Later, one dive from the NAVOCEANO series was used to correct this deficiency.

The results of this inspection, in general, revealed that the AUTEC range was very well designed and laid in the same manner. No unusual problems were discovered. Observers participating were from USN Underwater Weapons Engineering and Development Station, Newport; and International Telephone and Telegraph, Inc.; and David Taylor Model Basin.

Movies and Science

The catamaran proceeded to New Providence Island as a base. ALVIN made three shallow dives for underwater movies to be used in a National Educational Television (NET) program. This film (a children's and adult's version) will be shown this winter and next spring nationally on NET. WHOI and ONR will receive copies of this professional movie for their own use.

On August 23rd, Allyn Vine made his first deep dive in ALVIN. Currents, bottom topography, and temperature were observed on this dive. Dr. John Schlee, a member of the Geological Survey Agency (GSA), resident in Woods Hole, made two dives to observe the bottom geology to ascertain among other things, the structure of the Tongue of the Ocean (TOTO), an interesting geological phenomena. Core and rock samples were obtained. These have been dated to gain a better understanding of how TOTO was formed in ancient times.

NAVOCEANO Dive Series

A well planned series of scientific and engineering dives sponsored by NAVOCEANO were undertaken beginning on August 25th. The dives, 15 in number, their objective, and results are summarized in Appendix E.

It can be said that the experiments conducted in close association and under the direction of the personnel from NAVOCEANO was a very interesting and educational experience for both parties. Messrs. Frank Busby and Roger Merrifield, who supervised the diving operations in the field for NAVOCEANO were particularly well qualified to do this with forbearance and understanding of problems encountered, while at the same time accomplishing almost all of the objectives of the program; a rare feat in using this new oceanographic tool, the deep submersible. The program was carried out on schedule in spite of the close approach of two major hurricanes during the period, "Faith" and "Inez". The scientific results of the data collected during this series of dives is in preparation by NAVOCEANO.

Departure from the Bahamas

The USS ACCOKEEK (ATA 181) arrived on schedule and departed September 26 with the catamaran in tow. An uneventful passage to Woods Hole was accomplished with the exception of the last day out,

when a severe northeast storm slowed forward speed to almost zero. They finally arrived one day late in Woods Hole on 2 October 1966, having completed a successful cruise as planned. ACCOKEEK returned to home port, Philadelphia, without entering port.

Operations off New England

Upon arrival in Woods Hole, the catamaran and ALVIN was prepared for a series of dives south of New England. The first was actually conducted east of Chatham with Dr. Claes Rooth to measure the temperature microstructure at the thermocline. A 5' rod with thermistors at each end were placed in the hand of the mechanical arm and the temperature differences measured inside as ALVIN proceeded to a depth of 600'.

The next dive was made into Oceanographers Canyon, 120 miles southeast of Nantucket. Dr. James Trumbull was the observer. He was the first geologist to directly view a deep canyon in the Atlantic continental slope. Movies and stills were taken during the dive. The dive was shortened by the lack of navigation reference when the radar buoy, planted in 600' of water on the edge of the canyon, carried away. The M/V NARRAGANSETT again acted as escort during this expedition.

Fog and predicted bad weather terminated operations the following day and the catamaran returned to port. Blustery weather and a catamaran main engine casualty prevented a planned sortie the following week, so operations were concluded for 1966. ALVIN moved to Otis Air Force Base for annual refit, and the catamaran commenced a modification program in Woods Hole. These are still in progress at the end of this report period. (See Appendix A for details.)

New Construction

The second DSRV for ONR/WHOI and one for AUTECH was made possible by additional funds provided after the Aircraft Salvage Med. Bids had been taken by February and the contract for final design and construction was executed between the Naval Ship Systems Command (NAVSHIPS) and the Electric Boat Division (EB) of General Dynamics Corporation, Groton, Connecticut, in June. WHOI participated to a minor degree in the preparation of the final specifications and the bidders conference including an inspection of ALVIN at Otis Air Force Base in January. WHOI has since spent considerable time monitoring the design and participating in design conferences at EB and at NAVSHIPS.

Mr. Valentine Wilson was appointed the Senior Pilot in charge of the second WHOI DSRV and has been spending an increasing amount of his time in that activity. A crew chief for the vehicle has also been added to the staff. No further operating or support crew is being added because of budgetary limitations and uncertainty regarding the delivery date of the vehicle.

The two (2) hulls from the ALVIN contract with Litton Industries have been provided as government furnished equipment (GFE) for the two new DSRV's. This means that design of the pressure spheres is not a major part of this procurement.

Structural Design

At the direction of NAVSHIPS and ONR, WHOI took steps to design and procure Titanium spheres (Ti-6Al-4v), (Figure No. 15), to replace the nine buoyancy spheres (7178-T6 aluminum) and the six variable ballast spheres (6061-T6 aluminum) in ALVIN during this period. A contract was signed with Titanium Metals Corporation of America to provide these spheres. This will be the first known use of Titanium for major pressure-resistant structures in deep submersibles.

All of the new spheres were pressure-tested at the manufacturer's plant to 5000 psi (internal hydrostatic) and again at DTMB to 4500 psi (external hydrostatic). In addition two spheres from the production run were chosen as the worst structurally, to be tested to failure. The first one was tested during this report period and failed at 7800 psi after cycling 2000 times to 3000 psi in sea water at 45° F. The failure mode was believed to be a combination of buckling and creep at this pressure. See Reference No. 12 for details. The second will be tested to collapse early next year. The creep phenomena will be more fully investigated at that time.

Optical Investigation

A study in some depth was conducted by Lincoln Baxter, II, the results of which are reported in Report No. 6.

Research Submersibles Workshop

WHOI, encouraged by ONR, sponsored a Deep Manned Research Vehicle Workshop at Woods Hole on 21-22 November, 1966. This conference was organized for the purpose of getting together the scientific users of DSRV's, the DSRV operators and the DSRV program sponsors to explore the past experience and plan for future scientific use of this new oceanographic tool. Approximately 150 experts in the field representing the United States, France, Canada, and Great Britain attended. (Figure No. 12) A summary report is in preparation.

During this conference, the Assistant Secretary of the Navy for Research and Development, Dr. Robert Frosch, took the opportunity to present the Meritorious Public Service Citation to five members of the WHOI staff for their contribution to the success of Aircraft Salvage Med. (See Figure No. 13)

Cooperation from Other Activities

Assistance in the Aircraft Salvage Med. - the ALVIN group would not have been very useful without the assistance of many activities in the preparations for and carrying out of the mission in Spain. First of all, the personnel of Otis Air Force Base, particularly Lt. Col. Townsend, provided a great deal of help in preparing and loading the submarine and support equipment on the cargo aircraft. Sgt. Lorens of Dover AFB rendered invaluable assistance as "Cargo Master" both at Otis and at Rota, Spain.

It was also Otis AFB which provided the hangar for the annual refit period 1965-1966, as well as logistic support in the way of fork-lifts, heat, light, and other necessities.

Upon arrival in Rota, assistance in the reassembly of ALVIN was rendered by the naval personnel assigned to the base, the Submarine Squadron Staff and personnel of the USS HOLLAND, and particularly Capt. John Young, CO Naval Activities, Spain.

The CO and crew of PLYMOUTH ROCK (LSD 29), transported us to Palomares. The USS FORT SNELLING (LSD 30), which boarded us, supported us, commiserated with us and played a major role in the success of that operation, will never be forgotten by the ALVIN group embarked. Capt. I. A. Robinson, his officers and crew were so cooperative, solicitous and helpful that operations would have been almost impossible without them. Capt. Downing and the crew of the USS LINDENWALD (LSD 6), which transported ALVIN back to the U.S., will also be fondly remembered for their willingness to help.

USNS MIZAR provided a surface control center on many occasions and will always be remembered for the many times she got ALVIN down and back up safely. Mr. Chester Buchanen (NRL) was the person who developed and operated the system that accomplished this difficult mission and who was involved personally in the many long hours guiding ALVIN in the search and recovery.

The MSO's, first SKILL and then ABILITY, provided the surface control parties with everything necessary to bring about the successful discovery of the H-bomb in spite of the fact that this was an unprecedented (in their experience and ours) mode of operation. They willingly took advice from the "civilians" of the ALVIN group on control of the ship, plotting, etc., which got the job done.

Cooperative Program with Massachusetts Institute of Technology (MIT)

One naval officer, Lt. Ronald Booth, enrolled in the postgraduate course in Naval Architecture and Marine Engineering at MIT, spent the summer at WHOI assisting in study of special problems associated with the operation of DSRV's. This was a continuation of a cooperative program begun in 1965.

Assistance From USNUSL Research Detachment, and Naval Station, Bermuda

All of the logistic support necessary was provided by these two activities during ALVIN's deployment in Bermuda. The tug YTM 176 served again as our towing and tending ship to and from Argus Island with a great deal of skill. The support furnished by the Naval Station (Capt. Dawkins) was better than ever, and Cdr. Joseph Pinning and Mr. A. Donn Cobb of the Research Detachment at Tudor Hill were most cooperative.

Operational Assistance in the Bahamas

The main base at AUTEC, under the command of Cdr. Glenn Barney, provided berthing facilities and all necessary logistic support while operating in the AUTEC range. In addition, they supplied weather information and mail service when operating elsewhere in the Bahamas. Loan of a DECCA navigation receiver was a very important contribution to the success of our operations in the Bahamas.

Weather Information

The Fleet Weather Facility at Norfolk, Virginia provided necessary forecasts of weather during the operating year.

Personnel

The DSRVG continued to grow as more tasks were undertaken this year.

Full Time Employees

Staff

Earl E. Hays
William O. Rainnie, Jr. (also Chief Pilot)
Thomas B. Aldrich
William M. Marquet
James W. Mavor, Jr.
Thomas O. McClure
Frank P. Omohundro
Arnold G. Sharp
William S. Shultz

Charlotte G. Muzzey
Margaret P. Stern

Operations

Marvin J. McCamis
Valentine P. Wilson

Arthur C. Bartlett
Jess D. Baugh
Edward L. Bland, Jr.
George deP. Broderson
Theodore J. Curtis
Allan R. Davison

Operations, continued

Russell G. Graham
Richard D. Hafner
A. Larry Hunt
David H. Mason
Patrick J. O'Malley
Clifford L. Phippen
Chester R. Porembski
Carlos F. Porrata
Ferdinand C. Scaglione, Jr.

Resigned

Earl Bascome (December 1966)
Paul Byron (July 1966)
Ronald Hartman (August 1966)
Olin Knight (May 1966)
John Rozum (May 1966)
Maurice Spillane (September 1966)

Part-time

John Duff
Roger Forand
Joseph Henderson
Joseph Rokicki
Donald Williams

Associates

Lincoln Baxter, II
Ronald Booth, Lt., USN (MIT)
Jess H. Stanbrough
Allyn C. Vine
Joseph B. Walsh
Douglas C. Webb

Future Program

1. Scientific Program with ALVIN

The DSRV program at WHOI for calendar 1967 is planned to concern itself with scientific exploration of the deep sea, the purpose for which the ALVIN concept was undertaken.

In order to take advantage of the best weather patterns, a series of dives in the Bahamas is scheduled to commence the diving program; then in the Florida Straits; on the Blake Plateau; off the Chesapeake; south of Woods Hole on the continental slope, including geology dives into several canyons; and biology dives to investigate the benthic communities in deeper water; and to conduct other oceanographic experiments in situ.

2. Instrument Development

A major undertaking in the near future under the sponsorship of the NAVOCEANO, is to develop instrumentation for the more efficient scientific use of DSRV's such as: underwater navigation, environmental sensors and recorders, manipulative tools and accessories, and optical aids. This program should significantly enhance the ability of DSRV's to conduct useful scientific tasks in the deep ocean.

3. New DSRV

The completion of the design, the construction and test of the second DSRV will be closely followed. Provisions for support of this vehicle will be studied and planned for. Obtaining and training of the operating and support personnel will become an increasingly important activity.

4. New Developments

WHOI has considered the present state-of-the art and has determined that the most urgent needs in the next year are the design of a DSRVT capable of supporting at least one additional DSRV; and the design of a 20,000' DSRV for scientific exploration to the bottom of 95 percent of the world's oceans. It will be proposed that these two projects be undertaken just as soon as funds can be obtained.

In addition, investigation will continue into means of improving the capabilities of both the ALVIN and the catamaran within the budgetary limitations imposed.

The procedure for the collapse test of the second titanium sphere at DTMB will be prepared and the test witnessed.

Illustrations

- Figure 1 - ALVIN loading into the cargo airplane at Otis AFB
- Figure 2 - ALVIN and USS FORT SNELLING (LSD 30)
- Figure 3 - ALVIN in the well of the FORT SNELLING
- Figure 4 - USS SKILL (MSO 471)
- Figure 5 - USNS MIZAR
- Figure 6 - Underwater Terrain off Palomares
- Figure 7 - Bomb - underwater
- Figure 8 - Bomb - surface after recovery
- Figure 9 - CURV (Cable-controlled Underwater Recovery Vehicle)
- Figure 10 - The Catamaran, DSRVT-1, underway in Cape Cod Canal
- Figure 11 - ALVIN rigged for Science Dives
- Figure 12 - Deep Manned Research Vehicle Workshop
- Figure 13 - Meritorious Public Service Citation Awardees
- Figure 14 - Artists conception of the DSRV II
- Figure 15 - Drawing of Ti Sphere

Figure 1a - The C-133 at Otis Air Force Base with a portable van being loaded

Figure 1b - ALVIN loading into the C-133

Figure 1c - ALVIN from inside the C-133 during loading

Figure 2a - ALVIN at Palomares with USS BOSTON (CCG1)
and the ALVIN Mothership USS FORT SNELLING
(LSD 30). (Official U.S.Navy Photograph)

Figure 2b - FORT SNELLING with tailgate lowered.
L to R in background - ASR,MSO,ARS (Official U.S.
Navy Photograph)

Figure 3 - ALVIN in the well of FORT SNELLING preparatory to being lifted onto the hangar deck

Figure 4 - USS SKILL (MSO 471) (Official U.S.Navy Photograph)

Figure 5 - USNS MIZAR of the Naval Research Laboratory
(Official U.S.Navy Photograph)

Artist's conception based on sketches supplied by Dr. R. J. Smith of Naval Civil Engineering Laboratory: Dr. Smith's sources of information were the bathymetry survey prepared on the USNS DUTTON, discussions with members of the tactical analysis team on the staff of CTF 65, statements made by ALVIN and ALUMINAUT pilots, and bottom photographs supplied by ALVIN and MIZAR.

Figure 6 - The Terrain off Palomares, Spain where the H-Bomb was found. (Courtesy of NCEL, Port Hueneme)

Figure 7 - DISCOVERY!! The Parachute-shrouded Nose of the H-Bomb photographed by the E,G & G Camera Mounted on ALVIN

Figure 8 - The elusive H-Bomb on the deck of the USS PETREL (ASR 14), after successful recovery. L to R: Two Spanish officials; RADM W. S. Guest, USN, Commander Task Force 65; and MajGen. D. E. Wilson, USAF, Commander 16th Air Force. (Official U.S. Navy Photograph)

Figure 9 - The Cable-controlled Underwater Recovery Vehicle (CURV) developed and operated by the Naval Ordnance Test Station, Pasadena, that recovered the weapon. (Courtesy of NOTS, Pasadena)

Figure 10 - The Catamaran, DSRVT-1, in the Cape Cod Canal
after modifications during winter 1965-1966

Figure 11a - ALVIN rigged for geology dive in TOTO

Figure 11b - ALVIN rigged for geology dive into Oceanographic Canyon

Figure 12a - Working group at the Deep Manned Research Vehicle Workshop held at WHOI November 21-22, 1966

Figure 12b - One of the panels shown during the Workshop.
(Standing is H. E. Froehlich, Principal Designer
of ALVIN)

Figure 13 - Meritorious Public Service Citation presentation -
 Seated L to R: RADM. O. D. (Muddy) Waters, Oceanographer
 of the Navy; Dr. E. E. Hays, WHOI; The Honorable
 Robert A. Frosch, Assistant Secretary of the Navy for
 Research and Development
 Standing L to R: W. M. Marquet, WHOI; V. P. Wilson,
 WHOI; W. O. Rainnie, Jr., WHOI; M. J. McCamis, WHOI

Figure 14 - Artists Conception of the DSRV II being designed and constructed by the Electric Boat Division of General Dynamics Corporation for ONR/WHOI and AUTECH

Figure 15 - One of the Titanium Spheres manufactured by PSI for ALVIN.

APPENDIX A

Summary of Modifications - Refit 1965 - 1966 and 1966 - 67

1. ALVIN Modifications - Winter 1966 - 1967

The experience gained in operating ALVIN in a variety of missions and circumstances indicated the need for numerous modifications to improve safety, reliability, maintainability and capability. In addition, the planned program to replace the Aluminum spheres, used in the Variable Ballast and Fixed Buoyancy systems was directed by NAVSHIPS to be done this year. Titanium spheres having a designed collapse depth of over 15,000 ft., were designed and built. This made possible other modifications to simplify systems, make more thru-hull wires available for payload, and reduce weight. An additional objective followed in all of the modifications was that the changes made should contribute to the longer-range plan to qualify ALVIN for an operating depth of 9000 ft. The modifications described below are, at year's end, all in the process of accomplishment. Completion, final testing and evaluation will take place in 1967.

- a. Main Ballast Blow System -- this system was completely redesigned including the following major changes:
 - 1) The two 1/2 cu. ft. aluminum air flasks are removed; and one of the Titanium fixed buoyancy spheres, with capacity of 3 cu. ft., (vs 1 cu. ft.) is used for storage of 3000 psi compressed air.
 - 2) The large, heavy and unreliable motorized ball stop valve and smaller, solenoid list-control valves are replaced by two small (1 1/4" D x 2" L) solenoid valves which serve the dual functions of stop and list-control. These two small valves are relocated to the Variable Ballast oil-filled box.
 - 3) The Main Ballast box now contains only two vent valves and pressure transducers; therefore it is considerably reduced in size, and is relocated to the afterpart of the conning tower. In the former location, access for maintenance was gained only by removal of the entire sail structure.
 - 4) The two vent valves are modified to operate with a single solenoid coil. The two-coil and switching arrangement formerly used was a continuing source of malfunction.
 - 5) Nylon tubing is used to replace stainless steel tubing from the top of the tanks to the solenoid-operated vent valves and to the manually operated vent valve in the sail. The manual vent valve was changed from stainless steel to P.V.C. All of these changes were for weight saving, cost reduction and reliability.

- b. Additional buoyancy -- syntactic foam, of 37 lb/cu.ft. density, is being added to the bow superstructure to accomplish the following:
- 1) Provide additional buoyancy to permit carrying three people when the mechanical arm is attached.
 - 2) Provide protection for permanently-mounted equipment such as sonar, strobe light, and cameras.
 - 3) Provide mounting space and the necessary buoyancy for increased scientific instrumentation.
 - 4) Provide buoyancy for the future installation of two light-weight mechanical arms.
 - 5) Provide buoyancy for increased battery capacity.
- c. Variable Ballast System -- this system was extensively redesigned with the following major changes:
- 1) The Aluminum spheres are replaced by Titanium spheres.
 - 2) The large, heavy unreliable motorized ball valve is replaced by a two-way, solenoid-operated poppet valve.
 - 3) The two lower spheres have connections at their tops with tubing connecting to the four upper spheres; thus, the two lower spheres will fill completely before any fluid enters the upper spheres.
 - 4) The float switch chamber is being re-arranged and re-oriented to reduce the chance of pumping air from the spheres.
- d. Battery -- the type, capacity and arrangement are all being changed as follows:
- 1) A combination of Exide 12v and Cell-o-matic 2 v cells have been in use. These are being replaced by a single type designed for deep discharge in an attempt to improve the short life experienced with the present cells(<50 total cycles). The cell selected, on the recommendation of the manufacturer, is the Exide FH-17, a 6-volt, 158 amp-hr. battery. The measured capacity in the first three (3) cycles was 143 AH. We expect this to improve to 150 AH as the batteries age. For use with the new battery, a new vent-filter reservoir was locally designed.
 - 2) The new cells are arranged in three parallel strings of five batteries each to supply a 30-volt bus, and three parallel strings of ten batteries each to supply a 60-volt bus. Each of the three battery tanks contains one 30-volt string and one 60-volt string.
 - 3) A comparison of the weight and capacity of the new batteries versus the old is tabulated below:

(a) Characteristics of individual cells:

	Volt	A.H.Act	Wt.-Air	Wt.-H ₂ O	Dimensions - In.		
	DC	8 Hr. Rate	Lb.		W	L	H
Exide Commodore 72	12	60	44.0	25.3	6 5/8x10	1 1/8x8	1 1/4
Cell-O-Matic Olympic	2	105	14.5	7.7	2 1/8x 6	7/8x8	1/4
Exide FH-17	6	150	60.0	31.9	6 7/8x10	1 1/4x9	5/16

(b) Old and new Battery Arrangement

	No. of Cells/St.	No. of Strings	Total Cells	Wt. in Air Lb.	Wt. in Water Lb.	Amp. Hr. Cap.	KW. H. Cap.
Science (30v)	15	3	45	652	347	315	9.45
Control (30v)	15	2	30	435	212	210	6.30
Propulsion (60v)	5	6	30	1320	759	360	21.60
Old Arrg't Total	--	11	105	2407	1318	885	37.35
Science/Control (30v)	5	3	15	900	479	450	13.50
Propulsion (60v)	10	3	30	1800	957	450	27.00*
New Arrg't Total	--	6	45	2700	1436	900	40.50
New Arrg't Diff.	--	--	--	+293	+118	+15	+3.25
Change in %				+12.2	+ 9.0	+1.7	+8.7

* Since propulsion battery capacity has been the limiting factor in 90% of the dives to date, relatively more cells were added to propulsion.

We now expect to have about one additional hour of propulsion endurance at cruising speed.

(c) A comparison of the gain in capacity versus the weight penalty for the new battery arrangement does not appear to be entirely warranted unless one considers the expected improved life of the new cells (200 cycles minimum vs less than 50 cycles). This means that if the new batteries live-up to expectations, we will have to change batteries every other year instead of twice-a-year as we have in the past. This has been a major maintenance problem. In addition, the 12v Exide battery did not permit using it for the 30v banks. Thus two different cells were required.

- 4) The bus circuitry is simplified by replacing a 30-volt Science bus and a 30-volt Control bus with one 30-volt Auxiliary bus, and by arranging the batteries so all three tanks contain the same number and kind of cells.
- 5) To accomodate the physical dimensions of the new type battery, the battery trays were re-designed and modified. The resulting trays are slightly heavier; but are stronger and are not as susceptible of providing a grounding path.

- e. Battery Compensation System -- this system was redesigned to improve flow of venting gases and the flow of compensating oil, and to improve the safety of the system by separating each box vent system from each other.
- f. Main Sphere Electric Disconnects -- the oil-filled boxes, into which all wires were brought for connection to pins, were redesigned larger to facilitate making connections.
- g. Sample and Tool Trays -- during the year several designs of trays, as well as methods of attachment, have been tried. The most recent design is light-weight, may be dropped by a solenoid release, has sled-runner type supports to prevent catching on the bottom, and is readily viewed through the front window. (See Figure No.11)
- h. Weight-droppers -- during the year's operations a solenoid-operated weight-dropper designed by Benthos Co. was successfully tested. Now three weight-droppers of similar design, capable of dropping 250 lb. weights, are under procurement, in addition to a pinger-dropper. These will be used as follows:
 - 1) Descent Weight - a 200 lbs. weight (or less, depending on depth of dive) will be carried until near the bottom, then released to speed the descent without using power pumping an equal amount of Variable Ballast to achieve neutral buoyancy.
 - 2) Ascent Weight - a 100 lbs. weight will be carried until the Pilot desires to return to the surface, at which time the weight is dropped. A controlled ascent can be made without pumping the 100 lb. of Variable Ballast. This is also a back-up for the V.B. System that will permit return to a depth where the MB system becomes more effective. (Above 1000')
 - 3) Mechanical Arm Compensator - since Syntactic Foam is being added to permit carrying three people when the arm is attached, compensating weight must be carried on those dives in which the arm is left off. As an added safety feature, this weight will be droppable.
 - 4) Pinger-dropper -- a small, expendable 37 KC pinger will be carried externally. If the Pilot desires to mark a spot on the bottom and use it as a reference, he may drop the pinger, which is actuated upon release. At present if a 37 KC pinger is carried, its signals seriously interfere with the CTFM Sonar.
- i. Fiberglass Skin -- the fragile superstructure has been a continuing maintenance problem. The entire lower portion was redesigned to give it greater strength and to permit removal of small sections for much better access to other components. For example, the structure which contains the

flexible bags of the Variable Ballast system is made integral with the skin in that area. Thus it is now separately removable without disassembly of the submarine. Access panels are enlarged for better maintenance and repair; and all bolting edges are strengthened to prevent loss and improve maintainability. The present skin was porous and had absorbed a great deal of moisture making it heavier than desirable.

- j. Frame -- inspection of the frame at the start of the refit period revealed a number of small cracks in welds in the vertical members at the after end of the skids. Re-enforcing members were welded into place in the weak areas. Re-enforcing members are also being added between the forward end of the skids and the ring which supports the personnel sphere. The latter is being done to bear the load of the new syntactic foam being added to the bow.
- k. Hull Penetrators -- one penetrator containing six (6) coax cables and one penetrator containing six (6) shielded pairs of wires are being replaced by penetrators containing 18 single leads. This change will provide additional thru-hull wires for scientific instrumentation.
- l. Electric Circuits -- improved reliability at some expense in maintainability replacing pin connectors in some of the oil-filled boxes by hard-wiring between boxes.
- m. Battery Fuses -- to eliminate the possible hazard of the arc of a blowing fuse igniting the combination of hydrogen, oxygen and compensating oil present in the battery tanks, an investigation and test program was carried out. One obvious solution was to remove the fuses from the battery tanks; however this would be complex and expensive in the ALVIN arrangement. Negotiations with a fuse manufacturer were carried out to produce a fuse potted under vacuum with epoxy. Tests were conducted to determine:
 - 1) Whether the blowing characteristic is satisfactory.
 - 2) Whether the fuse could withstand submergence pressure.
 - 3) Whether the epoxy potting would successfully quench the arc when blowing.All the tests were satisfactory for the 150 amp size of fuse tested; an order was placed for sufficient 70 amp fuses for the 30-volt batteries and 150 amp fuses for the 60-volt batteries, plus some of each for spares and some 70 amps for testing. However, the latter did not test satisfactorily.*

*One of the 70 amp fuses continued to pass current after initially blowing. Investigation further revealed that the potting compound was a flammable type of epoxy. The potted fuse approach was abandoned at this time. The previously used sand-filled, oil-soaked fuses are being relocated to a position at mid-depth of the battery tanks.

- n. Sphere Internal Arrangement - a study was carried out and work is progressing to accomplish the following:
- 1) Improve accessibility to the side windows.
 - 2) Relocate the Pilot's seat from the starboard side to the centerline.
 - 3) Improve accessibility of controls and viewability of indicators and monitors for the Pilot when he is at the front window and the observers as well.

2. Catamaran Modifications Winter 1965-1966

During the period of trials with ALVIN during 1965 the concept of launching, recovering and servicing ALVIN with the catamaran was proved. The concept that the catamaran would be simply a working platform, always tended by other support ships providing berthing, towing service and tracking services, was changed. Thus at the start of 1966 the catamaran was in a shipyard undergoing a modification program to make it self sufficient for periods of about one week. Much of the program was carried out in Woods Hole by other contractors and by in-house effort. All features of the changes and new installations were engineered, coordinated and supervised by DSRVP personnel.

Following is a listing of the major work accomplished;

- a. All hull and steel superstructure was sandblasted and painted.
- b. The central sections of the starboard pontoon were insulated and outfitted with bunks and lockers to accomodate 22 men. Air conditioning and space heaters were installed.
- c. The watertight integrity of both pontoons was improved by adding watertight doors, hatches and scuttles.
- d. Bilge drain piping was improved, overboard hull fittings were improved, a fresh water distribution system was installed, and tank heaters were installed in the above-water fresh water tanks. Large dump valves were also installed in the fresh water tanks as a means of damage control. Fire hydrants were installed.
- e. The single outboard drive unit located forward between the hulls was replaced by two units of the same size. One unit was placed on a pedestal on the stern of each pontoon. The two units are controlled remotely from the new Pilot House.
- f. An additional cargo boom was added on the starboard side, and both booms were equipped with 2-speed electric winches.

- g. A surplus MK 14 gyrocompass system was installed with two repeaters in the new Pilot House and a pelorus repeater on each side.
- h. Aluminum access trunks with inclined ladders were installed to provide access for both personnel and cargo from the upper deck into each pontoon.
- i. Considerable weight reduction, to compensate for new weights being added, was achieved by cutting out the flange and five inches of the web of heavy internal frames in both pontoons.
- j. One 35 KW diesel-generator was replaced by a 60 KW diesel-generator and a new electric distribution system was installed.
- k. An aluminum Pilot House and mast were installed on top of the after arch. Boat davits were incorporated into the structure of the Pilot House to permit hoisting one Boston Whaler. The Pilot House was outfitted with an existing marine band transceiver, a Loran receiver, an existing precision depth recorder, an inexpensive radar, a PA and intercom system, two underwater telephone controls, a chart table and stowage, an engine control console, two gyro-repeaters, and a magnetic compass. A combination air-conditioner and heater was installed in the overhead.
- l. Space for many required functions was not available in the two pontoons; therefore a 40-ft. house trailer was specially outfitted and installed on the foredeck. This was an unhappy compromise; but, for the funds available, served the functions very well. The trailer was outfitted to contain an office, galley, dining area, shower, and head facilities.

Diversion of ALVIN to Spain provided additional time to make further improvements in the Catamaran. Sea trials showed that with light winds a speed of about 6.5 knots could be achieved; but that course-keeping and maneuvering in tight quarters with any wind was unsatisfactory. Model tests were conducted in the towing tank, resulting in the design and installation of "lee-boards" on the inboard side of each pontoon under the forward arch. Subsequent trials indicated considerable improvement in maneuverability against a wind had been achieved.

A Battery-handling platform was designed and installed on the hoisting cradle. This platform obviated the previous hazardous and laborious procedure of lifting ALVIN plus cradle with the "Holly Hoist", moving them both forward over the deck, and setting them up on 39" high pedestals just to remove batteries from ALVIN.

3. Catamaran Modifications Winter 1966-1967

As the year ended, engineering studies were underway to make further improvements in the Catamaran. These are occasioned by the following factors:

- a. Additional experience was gained in operating during the past season.
- b. Correction of known deficiencies, for which time had not been available, was desired.
- c. A contract had been awarded for the construction of a second submarine for WHOI, which is to be larger and heavier than ALVIN.

The modification program planned to be undertaken during this period was as follows:

- a. Weight Reduction - Continuation of the weight removal program begun last year to handle the second DSRV and to improve the range and habitability.
- b. Submarine Repair - With the addition of the battery removal system on the hoisting cradle last year, major repairs to the submarine no longer require lifting the whole submarine. Thus to save weight, the "Holly Hoist" has been removed and a derrick capable of lifting 1/2 of ALVIN at a time is being designed to replace it at considerable saving in weight as well as utility for other functions.
- c. Habitability - The temporary house trailer added last year was not adequate for the purpose and interfered seriously with conning of the ship in restricted waters. All of the functions are being built into compartments between the port and starboard hulls forward and under the main deck. Included in this construction are fuel tanks to increase the range from one week to two weeks of normal operations. Bunks are to be added to total 26 vs 18.
- d. Hoisting System - The hoisting system has to be completely overhauled with renewal of cables, etc. It is also intended to improve the safety of the system by tying the port and starboard hoisting drums together mechanically, and changing over to hydraulic drive. This was done primarily to improve safety of operation by removing a chain drive necessary with the design of the electric drive.
- e. Engine Room - it was found that the 35 KW Kohler generator was uneconomical to repair. In order to maintain commonality of equipment, a 6-71 GM, 60 KW Diesel generator set was installed. The increased capacity is necessary to handle the increased instrumentation and habitability load as well.

The hydraulic pump for the new systems was connected to the original 60 KW generator set engine. The electrical system now will consist of two (2) 60 KW gensets. A fuel transfer systems is planned to provide better control of trim.

- f. Steering System - The electrical steering system for the main engines was unsatisfactory in that it drifted badly. Separate hydraulic steering systems for each engine is planned. An automatic pilot will be added to this system when time and funds permit. These hydraulic systems will be made cross connectable to the main hydraulic system for emergency power.
- g. After Mast - Broken welds in the after mast indicate repairs or replacement to support the new RDF and Radar antennas. A new lightweight forward mast is to be added to meet Rules-of-the-Road requirements for height of navigation lights.
- h. Anchor Windlass - The anchor windlass is now located aft on the starboard hull and uses a mushroom anchor which is of little value in anchoring in coral sands. This is to be replaced by an anchor windlass and a Danforth anchor located in the bow and operated hydraulically. This is made possible by the removal of the forward house trailer.
- i. Photo-Wet Lab - Experience last year indicated we need an on-the-scene photo processing capability as well as a science wet-lab. This is to be constructed in the starboard hull.
- j. Air Conditioning and Freezer Space - In the hot and humid tropics, the air conditioning installed last year was entirely inadequate on the bridge, the starboard living quarters and in the mess hall-galley area. This is to be corrected by the addition of adequate capacity. The freezer space was not adequate and will also be improved. Storage spaces necessary for stowage of spare parts and corrodible stores will be dehumidified.
- k. Electronics
 - 1) Radar - the inexpensive radar set procured last year was almost useless for the service intended. A more powerful and sophisticated set will be procured for better surface navigation, avoidance of surface traffic and location of the submarine on the surface.
 - 2) SSB Radio - will give long range communications throughout the intended operating area. This will be installed. Licensing may be a problem.

- 3) RDF equipment to obtain bearings on radio signals for navigation as well as the submarine, if lost, is being procured and installed.
- 4) Sub Tracking - an improved transponder system for tracking the submarine independent of the UQC is being installed.
- 5) Echo Sounding - the PGR which has not been reliable since acquisition three years ago, is being replaced by a different model which is reputed to be simpler, therefore more reliable as well as being more compact and lightweight.

The result of the above modifications should make the Catamaran a somewhat more self-sufficient ship and a safer support platform. The tracking and navigation capability should be markedly better than previously.

APPENDIX B

Preparations for Shipment

The submarine was assembled except for the conning tower. A special shipping skid was built by Otis AFB personnel for sliding ALVIN into the aircraft - a C133. It was decided to remove the lift props in order to assure overhead clearance. It turned out this was not necessary; however both of these subassemblies were separately skid mounted for easy handling. The spare batteries were packed in special shipping boxes. Most all of the loose gear was placed in the vans with the exception of the battery handling gear.

The decision was made to take all five support vans for self-sufficiency. This was a fortunate choice as it took several days to get the proper voltage for charging batteries hooked up on the LSD's. In addition the LINDENWALD was a DC ship at a different voltage from the submarine. This also permitted packing most of the loose gear in them rather than separately boxing it. The new charging van was completed and tested prior to departure.

For reference in the event the information is needed in the future, the following loading was made. On the C141, a full jet aircraft from Charleston, S. C., the following cargo was loaded on February 1, 1966:

Conning Tower w/skid	Wt. 2,300
Electronic Van	11,000
Machine Shop Van	13,000
Batteries, Spares	1,275
	1,625
	1,625
O2 Bottles	350
Oil Drums	431
	432
	454
	454
	455
	455
Sling	400
Sling	40
Stand(Batt. Hoist)	250
Stand(Batt. Hoist)	250
Steel(Batt. Handling)	20
Steel(Batt. Handling)	20
Batt. Hand. Frame	100
Batt. Hand. Frame	110
Batt. Hand. Stand	300
Total	<u>35,346</u>

On the C133, a turbo-prop aircraft from Dover, Delaware, the following was loaded on January 31, 1966:

Utility Van	Wt.	7,150
Main Submarine Assembly		28,670, inc. skid 1500
Charging Shack		4,800
Power Van		14,920
Afterbody Upper Fwd.		560
Lift Props		<u>350</u>
Total		56,450

APPENDIX C

DEEP SUBMERGENCE RESEARCH VEHICLE ALVIN DIVE
SUMMARY

1 January - 31 December 1966

Year's Results

Test Dives	3
Working Dives	73
Working Hours Submerged	430:54
Average Working Submergence	5:54
Total Diving Depth	26818 Fathoms

Dive	Date '66	Location	Objective	Pilots	Observers	Max.Depth	Submerged
109	2/9	Spain	Test	McCamis Wilson	Marquet	40 '	1h20m
110	2/14	Spain	Search	Rainnie McCamis	None	1800 '	6h03m
111	2/15	Spain	Search	Rainnie Wilson	None	2100 '	6h03m
112	2/17	Spain	Search	McCamis Wilson	Hays	2000 '	7h00m
113	2/19	Spain	Search	McCamis Wilson	None	2300 '	7h01m
114	2/22	Spain	Search	Rainnie McCamis	None	2250 '	7h00m
115	2/23	Spain	Search	McCamis Wilson	Marquet	1700 '	3h32m
116	2/24	Spain	Search	Rainnie Wilson	Marquet	1550 '	6h47m
117	2/25	Spain	Search	McCamis Wilson	Hays	2300 '	7h20m
118	2/26	Spain	Search	Rainnie McCamis	Boykin ONR	2300 '	6h22m
119	3/1	Spain	Search	Rainnie Wilson	Andrews Cath.Univ.	2800 ' First found "track"	7h05m
120	3/2	Spain	Search	McCamis Wilson	Hays	3000 '	7h16m
121	3/3	Spain	Search	Rainnie McCamis	Mason	3200 '	6h47m
122	3/4	Spain	Search	Rainnie Wilson	Graham	2800 '	3h26m
123	3/7	Spain	Search	McCamis Wilson	Helm DSSP	2700	7h00m
124	3/8	Spain	Search	Rainnie McCamis	Henifin DSSP	750 '	6h28m
125	3/9	Spain	Search	Rainnie Wilson	Porembski	800 '	5h30m
126	3/12	Spain	Search	McCamis Wilson	Fox	2600 ' 2nd time on "track"	4h46m
127	3/13	Spain	Search	Rainnie McCamis	None	2700 '	7h18m
128	3/15	Spain	Search	McCamis Wilson	Bartlett	2550 ' Found weapon	10h23m
129	3/16	Spain	Recovery Assist	McCamis Wilson	None	2725 '	4h57m
130	3/18	Spain	Recovery Assist	McCamis Wilson	None	2775 '	7h26m
131	3/23	Spain	Recovery Assist	McCamis Wilson	None	2700 '	8h29m
132	3/24	Spain	Recovery Assist	McCamis Wilson	None	2700 '	7h27m
133	3/25	Spain	Search	McCamis Wilson	None	2900 '	8h12m

Dive	Date '66	Location	Objective	Pilots	Observers	Max.Depth	Submerged
134	3/26	Spain	Search	McCamis Wilson	None	2600'	7h01m
135	3/27	Spain	Search	McCamis Wilson	None	2500'	8h52m
136	3/28	Spain	Search	McCamis Wilson	None	2300'	6h54m
137	3/30	Spain	Search	McCamis Wilson	None	2950'	8h04m
138	3/31	Spain	Search	McCamis Wilson	Elliott Straza	2200'	6h17m
139	4/1	Spain	Search	McCamis Wilson	Boykin ONR	2800'	7h17m
140	4/2	Spain	Search	Rainnie McCamis	Martin OPNAV	2900'	9h18m
141	4/3	Spain	Recovery Assist	McCamis Wilson	None	2900'	7h11m
142	4/5	Spain	Recovery Assist	McCamis Wilson	None	2900'	4h13m
143	4/7	Spain	Observe Recovery	McCamis Wilson	None	1925'	3h03m
144	6/22	Woods Hole Harbor	Test dive	McCamis Porembski	Marquet	75'	Weapon recovered 53m
145	7/1	Bermuda Bay	Test dive	McCamis Wilson	Marquet	75'	1h10m
146	7/3	Argus Island	Photo Insp.	McCamis Wilson	None	3200'	5h03m
147	7/4	Argus Island	Photo Insp.	McCamis Wilson	Webb	5200'	5h05m
148	7/5	Argus Island	Photo Insp.	McCamis Wilson	Porembski	6100'	5h22m
149	7/10	Argus Island	Photo Insp.	McCamis Wilson	Mullarkey USNUSL	6100'	6h00m
150	7/11	Argus Island	Photo Insp.	McCamis Wilson	Broderson	6000'	6h16m
151	7/12	Argus Island	Photo Insp.	McCamis Wilson	Mullarkey USNUSL	5900'	5h38m
152	7/17	Off Castle Harbor	Biology	McCamis	Hessler	5850'	6h00m
153	7/18	Argus Island		McCamis Wilson	Cobb USNUSL	5950'	First deep science dive 5h27m
154	7/29	Off Andros	Photo Insp.	McCamis Wilson	Owen	5200'	6h03m
155	7/30	4 East Golden Cay	Photo Insp.	McCamis Wilson	Austin USNUWS	4350'	6h28m
156	7/31	1 East Golden Cay	Photo Insp.	Rainnie Wilson	Austin USNUWS	2400'	4h07m
157	8/4	5 East Andros	Photo Insp.	McCamis Wilson	Austin USNUWS	5450'	5h12m
158	8/5		Photo Insp.	Rainnie McCamis	Murray ITT	5150'	7h01m
159	8/6	2 East Andros	Photo Insp.	McCamis Wilson	Lamoureux USNUWS	2625'	4h58m

Dive	Date '66	Location	Objective	Pilots	Observers	Max.Depth	Submerged
160	8/7	Off Andros	Photo Insp.	Rainnie Wilson	Fine USNUWS	5050'	4h29m
161	8/12	TOTO	Photo Insp.	McCamis Wilson	Merriam DTMB	5625'	6h00m
162	8/15	Goulding Cay	Movies	McCamis Wilson		shallow	1h11m
163	8/17	Lyford Cay	Movies	McCamis Wilson		200'	2h18m
164	8/19	Lyford Cay	Movies	McCamis Wilson		shallow	2h44m
165	8/22	TOTO	Physical Oceano.	Rainnie	Vine	5850'	6h28m
166	8/23	TOTO	Geology	Wilson	Schlee	5550'	5h55m
167	8/24	TOTO	Geology	McCamis	Schlee	3250'	5h24m
168	8/26	TOTO	Visibility measure	Rainnie	Olson NAVOCEANO	2750'	5h11m
169	8/27	TOTO	Geology	Wilson	Busby NAVOCEANO	4100'	4h45m
170	9/1	TOTO	Soil Mechanics	McCamis	Rucker NAVOCEANO	3550'	5h12m
171	9/6	TOTO	Soil & Gravity	Rainnie	Delort NAVOCEANO	4900'	6h41m
172	9/8	TOTO	Activate Module	Wilson	Davison	5350'	6h38m
173	9/9	TOTO	Bottom Recon.	Rainnie	Huddell NAVOCEANO	4500'	6h31m
174	9/10	TOTO	Moor Insp.	McCamis Wilson	Merrifield NAVOCEANO	5550'	6h13m
175	9/11	TOTO	Array Insp.	McCamis Bland	Farquhar NAVOCEANO	5600'	6h28m
176	9/14	TOTO	Bottom profiling	Rainnie Porembski	Klein E,G & G	4900'	5h04m
177	9/16	TOTO	Bottom loss	Wilson	Breaker Taylor NAVOCEANO	4950'	5h16m
178	9/18	TOTO	Bottom loss	Rainnie	Breaker Taylor NAVOCEANO	4550'	5h46m
179	9/19	TOTO	Navigation test	McCamis Wilson	Marquet	4950'	6h34m
180	9/21	TOTO	Navigation test	Wilson	Merrifield Delort NAVOCEANO	150'	2h17m
181	9/22	Lyford Cay	Navigation test	McCamis Davison	Webb	80'	3h05m
182	9/23	Lyford Cay	Navigation	Rainnie	Merrifield Delort NAVOCEANO	50'	2h04m
183	10/14	29 East Chatham	Thermal gradient	Wilson	Rooth	615'	2h52m
184	10/15	Oceano-graphers Canyon	Geology	McCamis	Trumble	4800'	4h50m

END OF 1966 OPERATIONS

APPENDIX D

SUMMARY OF DIVES - Aircraft Salvops Med First Recovery Phase

Dive 129 March 16, 1966 - Mechanical arm mounted. Special stake taken to bottom on a 3/8" polypropylene messenger line, hand tended from small boat. The stake was driven in to the hilt near the weapon. A life line was to be run down the messenger by surface ship and then ALVIN was to attach it to the weapon, probably using a grappling hook in the parachute shrouds and risers. This attempt failed when the messenger-line stake was pulled out of the bottom attempting to run the lifting line down it. This was first of many successful acquisitions of the target by ALVIN using MIZAR's UTE to get in near vicinity and then using "clues" to find weapon.

Dive 130 March 18, 1966 - Tried to use special clamp, but 'chute and position of target prevented. Attempted to lower MIZAR's camera sled to near vicinity with line to be attached. Attempt was aborted when positioning sled by MIZAR became too difficult in current and surface conditions prevailing.

Note: Worsening weather and preparations for a new lifting rig delayed the next dive until March 23.

Dive 131 March 23, 1966 - Planted 37 KC pinger and Straza Transponder on 'chute with fish hooks. MIZAR dropped anchor with "poodle" within 70 feet of position and buoyed off. ALVIN attached grapnel on line from bottom of anchor to 'chute.

Dive 132 March 24, 1966 - Removed more shrouds and risers to more thoroughly hook in with grapnel. Unsuccessful in unraveling lines from "poodle" for more attachment. Made decision to lift by MIZAR. ALVIN surfaced. Line broke between anchor and weapon shortly after lift-off from the bottom as recorded on MIZAR's Precision Graphic Recorder (PGR).

APPENDIX E

Summary of NAVOCEANO Dives in TOTO

<u>N.O.Dive No.</u>	<u>WHOI Dive No.</u>	<u>Purpose</u>	<u>Results</u>
1	168	Photographic study of visibility while maneuvering near bottom. Special camera mounting and camera target required.	Intended data was collected, however, flat bottom was difficult to find for the experiment on this dive.
2	169	Geological Survey of terrain from deep water toward shallow. A core was taken.	Mission accomplished except that dive was terminated sooner than planned because of approach of hurricane Faith.
3	170	Study of Soil Mechanics. Two core samplers of different design with pingers and lights attached were dropped from surface by the catamaran.	ALVIN found the samplers and took pictures of same. Slope and density of bottom prevented penetration.
4	171	Soil Mechanics and Gravity Measurement. Two more samplers were dropped by the catamaran similar to dive No.3.	The samplers were again found by ALVIN five days after dropping using a 37 KC pinger to home on, and one light was released as designed and recovered by the catamaran. Gravity measurement was successfully made. Samplers did not penetrate flat bottom.
5	172	Correct the upright bail on one hydrophone in the AUTECH field found on previous series of dives. (This was not done on that dive because the mechanical arm was not carried).	Mission accomplished. NAVOCEANO "donated" this dive to AUTECH in the interest of supporting their (AUTECH) mission.

<u>N.O.Dive No.</u>	<u>WHOI Dive No.</u>	<u>Purpose</u>	<u>Results</u>
6	173	Bottom reconnaissance to find a spot to emplant future sensors.	Survey was conducted and suitable location in the proper depth of water were found and marked on the chart by Surface tracking party. Two cores were taken.
7	174	Inspection of the Deep Water Mooring in the middle of TOTO.	Unable to find western leg of moor and inspect it to the surface as planned. Some suspicion, not confirmed that mooring anchor is not attached to leg as supposed.
8	175	Inspection of environmental mooring, especially for biological fouling.	Location and inspection, including photos made of subsurface float and string to bottom anchor.
9	176	Acoustic bottom profiling with E, G & G recorder near the bottom in deep water.	2 1/2 miles were run and bottom profiling made successfully. Bottom penetration was achieved. Established feasibility of using this technique from DSRV's.
10	177	Acoustic bottom loss measurements at 50', 500', 2500' and 4500' above bottom in deep water.	Data collected at depths indicated. Still being analyzed.
11	178	Same as 10	Same as 10
12	179	Navigation in deep water. One triplane planted several days earlier was bracketed by catamaran with two more. ALVIN used Straza Sonar to acquire and navigate therefrom.	Successfully found nav aids (triplanes) and made various experiments to evaluate efficacy of using this economical deep water navigation system.

<u>N.O.Dive No.</u>	<u>WHOI Dive No.</u>	<u>Purpose</u>	<u>Results</u>
13	180	Precision underwater navigation system for photo surveys. Two transponders were surface planted in shallow water and circular paths run about them submerged.	System works well. With very little practice, pilots can maintain 1-3 foot accuracy on circular search patterns.
14	181	Precision underwater navigation system using "precision time" pinger emplaced on bottom in shallow water.	Results very similar to dive No. 13.
15	182	Same equipment and objective as Dive No.13 except attempt to run "straight line" search pattern.	Enough was learned to indicate system will work as designed. However, mechanical submarine difficulties with the variable ballast system coupled with poor transponder performance prevented good data collection.

Distribution List 3484

2	Commanding Officer Office of Naval Research 495 Summer Street Boston, Massachusetts 02210		Chief, Bureau of Ships Code 341 A Department of the Navy Washington, D. C. 20360
3	Director, Naval Research Laboratory Information Officer Technical Services Washington, D. C. 20390	1	Chief, Bureau of Ships Code 300 Department of the Navy Washington, D. C. 20360
2	Oceanographer U. S. Navy Oceanographic Office Library (Code 1640) Washington, D. C. 20390	2	Chief, Bureau of Ships Code 420 Department of the Navy Washington, D. C. 20360
2	Chief, Bureau of Weapons Department of the Navy Washington, D. C. 20390	1	Chief, Bureau of Ships Code 525 Department of the Navy Washington, D. C. 20360
1	U. S. Navy Electronics Laboratory Code 3140D San Diego, California 92152	2	Chief, Bureau of Ships Code 440 Department of the Navy Washington, D. C. 20360
1	U. S. Navy Electronics Laboratory Code 4320 San Diego California 92152	2	Department of Meteorology and Oceanography U. S. Naval Postgraduate School Monterey, California 93940
2	U. S. Navy Electronics Laboratory Code 2400, Attn: Librarian Technical Information Office San Diego, California 92152	2	Director U. S. Naval Underwater Sound Laboratory New London Connecticut 06320
2	Commander, Naval Ordnance Laboratory Librarian, White Oak Silver Spring Maryland 20910	3	Office of Naval Research Code 466 Undersea Programs Department of the Navy Washington, D. C. 20390
2	Superintendent U. S. Naval Academy Annapolis Maryland 21402	1	Office of Naval Research Code 416 Undersea Programs Department of the Navy Washington, D. C. 20390
1	Chief, Bureau of Ships Department of the Navy Washington, D. C. 20360	1	Office of Naval Research Code 439 Undersea Programs Department of the Navy Washington, D. C. 20390
1	Chief, Bureau of Ships Code 410 Department of the Navy Washington, D. C. 20360		
2	Commanding Officer & Director Naval Ship Research & Development Center Washington, D.C. 20007	2	Officer in Charge Annapolis Division Naval Ship Research & Development Center Annapolis, Maryland 21402

1	Dr. Edward Wenk, Jr.
Legislative Reference Service
Library of Congress
Room 203, Main Building
Washington, D. C. 20540	1	Director
Lamont Geological Observatory
Torrey Cliff
Palisades, New York 10964
1	National Academy of Sciences
National Research Council
2101 Constitution Avenue
Washington, D. C. 20037	2	Director
Southwest Research Institute
San Antonio, Texas
1	Commanding Officer and Director
Code L31
U. S. Civil Engineering Laboratory
Port Hueneme, California 93041	1	Professor T. P. Torda
Department of Mechanical Engineering
Illinois Institute of Technology
Chicago, Illinois 60616
1	Department of Naval Architecture and
Marine Engineering
Massachusetts Institute of Technology
Cambridge, Massachusetts 02139	1	Dr. William Rainey
National Academy of Sciences
2101 Constitution Avenue
Washington, D. C. 20037
2	Dr. C. M. McKinney
Defense Research Laboratory
University of Texas
Austin, Texas 78712	1	Mr. J. G. Wenzel
Lockheed Missile & Space Agency
Sunnyvale, California 94086
2	Director
Marine Physical Laboratory
Scripps Institution of Oceanography
La Jolla, California 92038	1	Grumman Aircraft Engineering Corporation
Engineering Library Plant #25
Bethpage, Long Island, New York 11714
1	Director, Marine Laboratory
University of Miami
1 Rickenbacker Causeway
Virginia Key
Miami, Florida 33146	1	President
Bell Telephone Laboratories
Whippany, New Jersey 07981
1	Director
Hudson Laboratories
145 Palisades Street
Dobbs Ferry, New York 10522	2	Electric Boat Division
General Dynamics Corporation
Groton, Connecticut 06340
2	Director
Applied Physics Laboratory
University of Washington
Seattle, Washington 98105	1	ALUMINAUT Project Coordinator
Reynolds Metals Company
Reynolds Metals Building
Richmond, Virginia 23218
1	Director
Ordnance Research Laboratory
Pennsylvania State College
University Park, Pennsylvania 16802	1	Mr. Joseph D. Malloy, President
Hydrosystems, Inc.
19 Engineers Lane
Farmingdale, New York 11735
1	Commander, USNOTS
Pasadena Annex
3202 East Foothill Blvd.
Pasadena, California 91107	1	H. I. Thompson Fiber Glass Company
Supervisor, Structural Development,
Materials Research Division
1600 West 135th Street
Gardena, California 90249
	ATTN: Pasadena Annex Library (Code P80962)		Chesapeake Bay Institute
The Johns Hopkins University
Macaulay Hall
Baltimore, Maryland 21218
			Commanding Officer
AUTC Headquarters
West Palm Beach, Fla. 33406

Woods Hole Oceanographic Institution
Reference No. 67-23

DEEP SUBMERGENCE RESEARCH CONDUCTED DURING THE PERIOD 1 JANUARY
THROUGH 31 DECEMBER 1966. 23 pages. April 1967. Contract Nonr-3484(00)
NR 260-107.

The Deep Submergence Research Program at Woods Hole Oceanographic
Institution (WHOI) entered into the first full operational year during
1966. ALVIN and the support catamaran underwent modification and over-
haul during the winter months.

ALVIN played a key role in the successful recovery of an H-Bomb
lost in the sea off Palomares, Spain. This operation is reported in
some detail. ALVIN then embarked on a series of dives supported by the
catamaran. One series off Bermuda was to inspect the ARTEMIS array.
Transit was then made to Tongue-of-the-Ocean (TOTO) in the Bahamas.
There portions of the AUTEK range were inspected, several WHOI science
dives were made, and a diving program carried out for the Naval Oceano-
graphic Office (NAVOCEANO).

After tow back to Woods Hole, two science dives were made and both
ALVIN and the catamaran went into an extensive refit and inspection
period. The plans for this activity are reported in some detail.

A new ALVIN-type submersible is under design and construction at
Electric Boat Division of General Dynamics Corporation.

1. DSRV ALVIN
 2. Deep Submergence Research
 3. 6,000 foot Research Submarine
 4. Instrumentation for Research Submarine
 5. Dives of ALVIN
 6. DSRV Tender
 7. Aircraft SALVOPS MED
 8. Naval Oceanographic Office
 9. Science Dives
 10. Underwater Navigation
- I. Hays, Earl E.
 - II. Rainnie, W. O.
 - III. Nonr-3484(00) NR 260-107

This card is UNCLASSIFIED

Woods Hole Oceanographic Institution
Reference No. 67-23

DEEP SUBMERGENCE RESEARCH CONDUCTED DURING THE PERIOD 1 JANUARY
THROUGH 31 DECEMBER 1966. 23 pages. April 1967. Contract Nonr-3484(00)
NR 260-107.

The Deep Submergence Research Program at Woods Hole Oceanographic
Institution (WHOI) entered into the first full operational year during
1966. ALVIN and the support catamaran underwent modification and over-
haul during the winter months.

ALVIN played a key role in the successful recovery of an H-Bomb
lost in the sea off Palomares, Spain. This operation is reported in
some detail. ALVIN then embarked on a series of dives supported by the
catamaran. One series off Bermuda was to inspect the ARTEMIS array.
Transit was then made to Tongue-of-the-Ocean (TOTO) in the Bahamas.
There portions of the AUTEK range were inspected, several WHOI science
dives were made, and a diving program carried out for the Naval Oceano-
graphic Office (NAVOCEANO).

After tow back to Woods Hole, two science dives were made and both
ALVIN and the catamaran went into an extensive refit and inspection
period. The plans for this activity are reported in some detail.

A new ALVIN-type submersible is under design and construction at
Electric Boat Division of General Dynamics Corporation.

1. DSRV ALVIN
 2. Deep Submergence Research
 3. 6,000 foot Research Submarine
 4. Instrumentation for Research Submarine
 5. Dives of ALVIN
 6. DSRV Tender
 7. Aircraft SALVOPS MED
 8. Naval Oceanographic Office
 9. Science Dives
 10. Underwater Navigation
- I. Hays, Earl E.
 - II. Rainnie, W. O.
 - III. Nonr-3484(00) NR 260-107

This card is UNCLASSIFIED

Woods Hole Oceanographic Institution
Reference No. 67-23

DEEP SUBMERGENCE RESEARCH CONDUCTED DURING THE PERIOD 1 JANUARY
THROUGH 31 DECEMBER 1966. 23 pages. April 1967. Contract Nonr-3484(00)
NR 260-107.

The Deep Submergence Research Program at Woods Hole Oceanographic
Institution (WHOI) entered into the first full operational year during
1966. ALVIN and the support catamaran underwent modification and over-
haul during the winter months.

ALVIN played a key role in the successful recovery of an H-Bomb
lost in the sea off Palomares, Spain. This operation is reported in
some detail. ALVIN then embarked on a series of dives supported by the
catamaran. One series off Bermuda was to inspect the ARTEMIS array.
Transit was then made to Tongue-of-the-Ocean (TOTO) in the Bahamas.
There portions of the AUTEK range were inspected, several WHOI science
dives were made, and a diving program carried out for the Naval Oceano-
graphic Office (NAVOCEANO).

After tow back to Woods Hole, two science dives were made and both
ALVIN and the catamaran went into an extensive refit and inspection
period. The plans for this activity are reported in some detail.

A new ALVIN-type submersible is under design and construction at
Electric Boat Division of General Dynamics Corporation.

1. DSRV ALVIN
 2. Deep Submergence Research
 3. 6,000 foot Research Submarine
 4. Instrumentation for Research Submarine
 5. Dives of ALVIN
 6. DSRV Tender
 7. Aircraft SALVOPS MED
 8. Naval Oceanographic Office
 9. Science Dives
 10. Underwater Navigation
- I. Hays, Earl E.
 - II. Rainnie, W. O.
 - III. Nonr-3484(00) NR 260-107

This card is UNCLASSIFIED

Woods Hole Oceanographic Institution
Reference No. 67-23

DEEP SUBMERGENCE RESEARCH CONDUCTED DURING THE PERIOD 1 JANUARY
THROUGH 31 DECEMBER 1966. 23 pages. April 1967. Contract Nonr-3484(00)
NR 260-107.

The Deep Submergence Research Program at Woods Hole Oceanographic
Institution (WHOI) entered into the first full operational year during
1966. ALVIN and the support catamaran underwent modification and over-
haul during the winter months.

ALVIN played a key role in the successful recovery of an H-Bomb
lost in the sea off Palomares, Spain. This operation is reported in
some detail. ALVIN then embarked on a series of dives supported by the
catamaran. One series off Bermuda was to inspect the ARTEMIS array.
Transit was then made to Tongue-of-the-Ocean (TOTO) in the Bahamas.
There portions of the AUTEK range were inspected, several WHOI science
dives were made, and a diving program carried out for the Naval Oceano-
graphic Office (NAVOCEANO).

After tow back to Woods Hole, two science dives were made and both
ALVIN and the catamaran went into an extensive refit and inspection
period. The plans for this activity are reported in some detail.

A new ALVIN-type submersible is under design and construction at
Electric Boat Division of General Dynamics Corporation.

1. DSRV ALVIN
 2. Deep Submergence Research
 3. 6,000 foot Research Submarine
 4. Instrumentation for Research Submarine
 5. Dives of ALVIN
 6. DSRV Tender
 7. Aircraft SALVOPS MED
 8. Naval Oceanographic Office
 9. Science Dives
 10. Underwater Navigation
- I. Hays, Earl E.
 - II. Rainnie, W. O.
 - III. Nonr-3484(00) NR 260-107

This card is UNCLASSIFIED

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Woods Hole Oceanographic Institution Woods Hole, Massachusetts		2a. REPORT SECURITY CLASSIFICATION Unclassified	
		2b. GROUP	
3. REPORT TITLE DEEP SUBMERGENCE RESEARCH CONDUCTED DURING THE PERIOD 1 JANUARY THROUGH 31 DECEMBER 1966			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Progress Report			
5. AUTHOR(S) (Last name, first name, initial)			
6. REPORT DATE April 1967		7a. TOTAL NO. OF PAGES 23	7b. NO. OF REFS 12
8a. CONTRACT OR GRANT NO. Nonr-3784(00) NR 260-107		9a. ORIGINATOR'S REPORT NUMBER(S) WHOI Reference No. 67-23	
b. PROJECT NO.			
c.		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.			
10. AVAILABILITY/LIMITATION NOTICES Each transmittal of this document outside of the agencies of the U.S. Government must have prior approval of the Office of Naval Research, Boston Branch.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Office of Naval Research (Code 466) Department of the Navy Washington, D.C.	
13. ABSTRACT The Deep Submergence Research Program at Woods Hole Oceanographic Institution (WHOI) entered into the first full operational year during 1966. ALVIN and the support catamaran underwent modification and overhaul during the winter months. ALVIN played a key role in the successful recovery of an H-Bomb lost in the sea off Palomares, Spain. This operation is reported in some detail. ALVIN then embarked on a series of dives supported by the catamaran. One series off Bermuda was to inspect the ARTEMIS array. Transit was then made to Tongue-of-the-Ocean (TOTO) in the Bahamas. There portions of the AUTECH range were inspected, several WHOI science dives were made, and a diving program carried out for the Naval Oceanographic Office (NAVOCEANO). After tow back to Woods Hole, two science dives were made and both ALVIN and the catamaran went into an extensive refit and inspection period. The plans for this activity are reported in some detail. A new ALVIN-type submersible is under design and construction at Electric Boat Division of General Dynamics Corporation.			

14.	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	1. DSRV ALVIN 2. Deep Submergence Research 3. 6,000 foot Research Submarine 4. Instrumentation for Research Submarine 5. Dives of ALVIN 6. DSRV Tender 7. Aircraft SALVOPS MED 8. Naval Oceanographic Office 9. Science Dives 10. Underwater Navigation						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.